

Continue



Olympus oer pro user manual

|

 |

--
--
--
---|
| User Manuals, Guides and Specifications for your Olympus OER-Pro Laboratory Equipment, Medical Equipment. Database contains 2 Olympus OER-Pro Manuals (available for free online viewing or downloading in PDF): Operation manual. Page 1 Instructions Endoscope Reprocessor OER-Pro For details on installation and setup, refer to "Instructions - Installation Manual". Page 2 Supplement to OER-Pro Instruction Manual Some functions are unavailable depending on the software version. Check if the software version number is displayed after the power activation and opening the water faucet". If the software version number is not displayed after the power activation, an older software version is installed and the following functions are unavailable. Page 3 Inspecting and replacing the detergent tank. Inspecting and replenishing alcohol.....Inspecting the mesh filters Inspecting for disinfectant solution odor.....Inspection of leak test function.....3.10 Checking the disinfectant solution concentration level ... 3.11 Inspecting the printer paper rollENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 4 Display of the total number of times the disinfectant solution was loadedDisplay the total cycle count of the equipment..... Air purgeRinsing Alcohol flushing6.10 Emergency stop and automatic processing after stopping 6.11 Print function setup 274 Troubleshooting and 274 Troubleshooting guide OER-Pro Return Appendix Priming function for troubleshooting 288

 |
| Symptom chart Shipping environment Operating environment Specifications EMC information Detergents, Disinfectants, and Chemical indicators informationENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 6 Contents ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 7 The meaning(s) of the symbol(s) shown on the component packaging, the back cover of this instruction manual and/or this equipment are as follows: Refer to instructions, Caution, hot surface Endoscope reprocessor Manufacturer Authorized representative in the European Community Lot number Serial number Date of manufacture ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 8 Labels and Symbols Safety-related labels and symbols are attached to the equipment at the locations shown below. If labels or symbols are missing or illegible, contact Olympus. [Front panel] ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 9 Labels and Symbols UDI label A label required by some countries' regulations regarding identification of medical device also known as Unique Device Identification (UDI). RFID marking ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 10 SON D'ENDOSCOPES, VEUILLEZ COMMUNIQUER AVEC OLYMPUS. CE TABLEAU EST FONDÉ SUR LES RENSEIGNEMENTS DISPONIBLES AU JJ MM AAAA. VEUILLEZ COMMUNIQUER AVEC OLYMPUS EN CE QUI CONCERNE. NANT LES ENDOSCOPES MIS SUR LE MARCHÉ APRÈS LE JJ MM AAAA OU POUR TOUTE QUESTION CONCERNE. NANT LES COMBINAISONS D'ENDOSCOPES INDIQUÉES DANS CE TABLEAU. Page 11 TROIR NE SE FERME PAS. ■TOUJOURS UTILISER LA SOLUTION DESINFECTANTE Placed detergent reservoir in the wrong direction can damage the device or clog the ventilation openings, causing malfunction. Flasks of disinfectant solution must be placed correctly to avoid leakage or contamination. Important safety information: never block the ventilation openings on the left side, as this could lead to equipment failure. Disinfectant solutions and alcohol require proper handling, including wearing a face mask, gloves, and protective clothing to prevent skin contact and aspiration. The device should only be used with compatible endoscopes and connecting tubes, as listed in the user manual. Regular maintenance and inspection are necessary to ensure the device functions properly. Expired disinfectant solutions must be disposed of according to local regulations, and all applicable national and state guidelines should be followed when disposing of the equipment and accessories. 1. Cleaning Fluid - Refers to filtered water with detergent used during cleaning process. 2. Disinfectant Solution - Olympus-validated concentrated solution or ready-to-use, use Olympus-validated list of solutions. 3. Reprocessing Programs - Selectable by user, program [1] has fixed pre-set time for cleaning and disinfection. 4. Check Package Contents - Inspect each item for damage, do not use device if damaged, contact Olympus immediately. 5. Air Filter [MAJ-1497] & Water Filter [MAJ-823/824] & Water Tray [GC601400] 6. Accessories - Alc tank, circulation port mesh filters (GN424800/GC574000), retaining rack (MAJ-1970), drain port mesh filter (GT115400/GC220100). 7. Test Strip Forcets (GC601300/GL366300/GT867700) & Water Supply Piping Disinfection Hose 8. Connector Jig, Spare Fuses (2). User ID master card, Scope ID master card. 9. Checking Package Contents - Manuals, List of Compatible Instructions-Operation Manual, Tubes OER-Pro Quick Reference Guide OER-Pro Operation Guide. 10. Contact Olympus for information on alcohol remaining in device. Marks for confirming disinfectant solution level in equipment are crucial. Washing case mount ensures accessories, including valves, are properly stored. The ENDOSCOPE REPROCESSOR OER-Pro Operation Manual explains communication status indicators and button functions. For details on print function setup, refer to Section 6.11. The device performs disinfection tests and leak checks. Temperature displays show values equal to or higher than 20°C (68°F). Total cycles and usage data are also displayed. Internal water, gas, and air filters maintain equipment cleanliness. Recommended products include EndoQuick Alkaline detergent and Olympus-validated concentrated disinfectant solution. Contact Olympus for more information on these products. Additionally, the manual lists other products from trusted suppliers, such as Adbioh 1.8 Chutaldehyde Indicators and ACECIDE test strips. Finally, it highlights the importance of inspecting leak levels and disinfectant levels before each reprocessing cycle. Inspecting the printer paper roll and communication status are crucial steps before using the Endoscope Reprocessor OER-Pro Operation Manual. To ensure proper function, Olympus recommends wearing protective gear and running equipment in well-ventilated areas when handling disinfectant solution and alcohol. Before use, inspect the equipment for any irregularities or damage. Check connectors, tubes, and detergent tanks to prevent ineffective reprocessing or damage to the endoscope. Make sure to properly fix connectors and O-rings, and replace any damaged components. In addition, check the detergent tank level regularly. If it reaches "MIN", replace the tank within a few operations. Remember to contact Olympus for validated detergents and instructions on proper use. When replacing the detergent tank, ensure that the new one is securely attached with the connector. Wipe any excess detergent from the connector and dispose of used tanks according to local regulations. Regularly remove and replace the alcohol in the alcohol tank at least once a week to maintain its quality. Before handling alcohol, carefully read the precautions for use and follow instructions. Inspecting and maintaining the equipment is crucial for proper functioning and reprocessing of endoscopes. Any irregularities or damage can lead to ineffective reprocessing or damage to the endoscope. Always contact Olympus if you encounter any issues or have questions about the Endoscope Reprocessor OER-Pro Operation Manual. Before alcohol flushing is performed when the level reaches "MIN", decrease and add alcohol as described in "Addition of alcohol". Figure 3.10 If alcohol flushing is executed when no alcohol is present, the equipment will stop and display an error code [E93]. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 56 Push the lock lever on the connector of the tube connected to the cap on the alcohol tank to detach the tube. Lock lever Alcohol tank Figure 3.12 Remove the alcohol tank and put it in a sink or other tub. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 57 After adding the alcohol, replace the cap on the alcohol tank. Line Figure 3.14 The amount of alcohol required to fill the tank up to the level line is about 500 ml (approximately 16 ounces), enough for about 10 alcohol flushes). ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 58 Connect the tube that was originally connected to the cap. Alcohol tank Ventilation tube Figure 3.15 Turn the connector to correct the tube orientation as shown below. Confirm that the tube is not bent. Connector Figure 3.16 Close the detergent/alcohol drawer. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 59 Step up on the foot pedal to open the lid. Remove the mesh filters from the reprocessing basin. Drain port mesh filter Circulation port mesh filters Figure 3.17 Check that the mesh filters are not clogged by a foreign object. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 60 Activate the room's ventilation system. Check that there is no abnormal disinfectant solution odor coming from the equipment or its surroundings. If the odor increases after replacement of the gas filters, contact Olympus. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 61 Olympus. Endoscope leak testing can be performed outside the OER-Pro, as per existing labeling, or can be performed in the OER-Pro. When the leak test is performed with the OER-Pro, follow the procedure in Section 4.7. "Leak test"... Page 62 Close the lid by pushing it until it clicks. Press the FUNC SEL button on the subcontrol panel to select "LEAK TEST". Figure 3.19 Press the FUNC START button on the subcontrol panel to start the water supply. Figure 3.20 ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 63 Wipe off any water on upside of the leak test connector (black) in the reprocessing basin with a clean cloth. Connect the leak test air tube connector (black) [MAJ-821] to the reprocessing basin's leak test connector (black). Figure 3.22 ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 64 Figure 3.23 Disconnect the leak test air tube from the alcohol tank's leak test connector. Wipe another leak test connector (black), confirm a supply by repeating from Step 7 to 10. Figure 3.24 ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 65 Clean required items (FDA-cleared chemical indicator (test strip) Drain connector (should be dry) Cup-shape container with a capacity of about 200 ml, such as a beaker (should be dry) Clean cloth Table 3.8 ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 66 If disinfectant solution leaks out of the disinfectant removal port when the rubber cap has been removed, immediately reattach the rubber cap and follow the procedure in Section 8.1. "Troubleshooting guide" on page 274. If leaking does not stop, contact Olympus. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 67 To reset the OER-Pro reprocessor, press [PUSH] on the front door and remove the rubber cap from the disinfectant port. Insert the drain connector into the disinfectant port until it clicks (See Figure 3.26). Rinsing the drain connector thoroughly in running water and store it safely once dry. When using the OER-Pro, inspect personal protective equipment regularly for damage and replace it before use. Refer to page 70 for more information on the TIME/CODE display on the main control panel. If the disinfectant solution fails to meet
the recommended concentration, stop the reprocessing process immediately and replace the solution (see page 72). When restarting the reprocessing of an endoscope, begin from Section 4.4. "Scope ID detection" on page 84. For issues with external devices, check the power supply and connections between devices. If problems persist, contact Olympus for assistance. The OER-Pro can store up to 60 reprocessing data records (see page 76). Chapter 4 of the manual outlines reprocessing operations, including the use of gas filters and ventilation when using disinfectant solution and alcohol. Wear protective gear, such as a face mask, gloves, and protective clothes, to minimize exposure risks. The OER-Pro reprocessor requires manual cleaning prior to processing in the device. According to the instruction manual for MAJ-1904, follow these steps: Check if the lamp is blinking and contact Olympus immediately. If unsure when the lamp started blinking, do not use the device and reach out to Olympus instead. If a problem persists after turning the power switch back on, try resetting it and contacting Olympus if necessary. Before reusing the device, ensure the power switch is off and unplug the power cord from both the device and the power outlet. For emergency cleaning represented in the OER-Pro manual, cleaning is required prior to processing. The modified procedure involves actions such as flushing channels with alcohol, read the precautions carefully and use it as instructed. Finally, close the lid, ensure the power switch is ON, connect the provided syringe and tube, and disconnect the ventilation tube from the guide of the alcohol tank. From the cap on the alcohol tank, take out the tank and put it back in the drawer with the ventilation tube inside the guide. Figure 4.48 - Page 130 If you get this far without a problem, you're good to go. But if the error code [E93] shows up again, something's wrong with your device. Don't use it anymore and call Olympus. Take off the connector jig from the reprocessing basin, wipe it clean with some sterile gauze, and put it away in a dry place. Page 131 Before using the detergent, read the warnings carefully and follow the instructions. Make sure you know what to do if you get any on your skin. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 132 Turn off the power switch and make sure everything is stopped. Open the lid with the foot pedal and attach the provided syringe and tube. Figure 4.50 ... Page 133 Hold the tube at the nozzle with your fingers and disconnect it from the detergent nozzle. Figure 4.52 Rinse the syringe and tube thoroughly in running water, dry them well, and store them in a clean place. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 134 If you're reprocessing two endoscopes at once, fix any problems with one of them before moving on to the next. Page 135 Keep your endoscopes and valves in a dry place. Take out the air tubes from the reprocessing basin, wipe off any water with some sterile gauze, and put them away in a clean place. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 136 PRINT TODAY --- PRINT ALL --- Print option can print out the --- Print option cannot print out the subject error result subject error result Table 4.3 ... Page 137 Don't get your printer wet or it might break. Always keep the cover closed. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 138 Store the printer in a cool, dark place. Keep it away from NOX, SOx, and O (ozone). Page 139 If you see red lines on both sides of the paper roll during printing, replace it. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 140 You can't print everything. See Table 4.6 for details. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 141 PRINT TODAY Press INFO SEL button on subcontrol panel to print out the Print option cannot print out the subject error result subject error result Table 4.8 ... Page 142 "PRINT 1. Pressing FUNC START button will initiate reprocessing, allowing for multiple printouts until the next process is initiated. 2. Refer to page 145 for printing information about "Reprocessing Result" and page 146 for "Error Results". 3. The device cannot print records of completed or incomplete sub-independent processes or error occurrences during standby operation; refer to Table 4.10 for details on error result printing function. 4. When printing is finished, the buzzer beeps and paper feed stops; ensure that printed information is accurate by cutting and reattaching paper. 5. If an error code [E94] is encountered after a print stop, do not clear the error code but replace the printer paper roll instead. 6. "Error Result" records incomplete reprocessing due to errors during processing; refer to page 146 for printing information on this topic. 7. The buzzer beeps and paper feed stops upon completion of printing; ensure accuracy by cutting and reattaching printed parts. 8. If an error code [E94] is encountered after a print stop, do not clear the error code but replace the printer paper roll instead. 9. In cases where RFID function has not been enabled at factory, serial numbers, model names, user number, and user name columns will be left blank. 10. Before changing date and/or time setting, print records of past stored information using print function; otherwise, device malfunction may occur due to irregularities such as water leakage or electric shock. Remove mesh filters from reprocessing basin, drain port, and circulation port. Clean mesh filters in running water using brush, then attach them back. Ensure fluid level sensor covers are attached after cleaning to avoid malfunction. Check disinfectant solution temperature by pressing INFO SEL button on subcontrol panel. Temperature should be displayed on TEMP/C display. Do not block ventilation as it can cause device malfunction and hinder deodorization. Heating disinfectant solution to 20C (68F) is necessary for the device by pressing the FUNC SEL button and select "AIR PURGE". Wait until the water flow stops, then press the STOP/RESET button to disconnect the filter tubes. 8. When using the new water filter, place the filter tube into the connector above the water filter housing until it clicks, but do not connect anything below the housing. 7.19 ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Chapter 7 Routine Maintenance. 1. Leak test the system by pressing the FUNC SEL button and selecting "LEAK TEST" from the subcontrol panel. 2. Close the front door and rinse the filter tube with running water, then dry it completely and store in a clean place. 3. Refer to Section 7.3 on page 202 for disinfecting the water supply piping instructions. Rinse water quality testing: Olympus recommends performing microbiological sampling right after water supply piping disinfection if the device has not been used for more than 14 days, or at least once a month with per hospital policy. Disinfectant solution management - Disconnect tubes from connectors before disinfecting the water supply piping. 4. Drain and replace disinfectant solution after water supply piping disinfection Maintenance steps: 1. Close the lid and press the FUNC SEL button to select "DISE LINES" on the subcontrol panel. 2. Hold the tube side end of the filter tube and insert it into a container, then connect the other end to the connector above the water filter housing. 3. If the temperature of the disinfectant solution is below 20°C (68°F), heat it to 20°C (68°F). 4. After heating, reconnect the tubes and restart the countdown on the TIME/CODE display. Important note: The system uses a diaphragm pump, resulting in gentle fluid flow that meets standards. Final steps: 1. Close the lid by stepping on the foot pedal. 2. When disconnecting the water supply piping disinfection hose, cover the end with a waterproof glove to prevent splash. Microbiological surveillance: Perform testing as required by your hospital's policy, or right after performing water supply piping disinfection. 4. When using disinfectant solution and alcohol, Olympus recommends using gas filters and operating in a well-ventilated area. Wear protective gear like a face mask, gloves, and clothes to minimize aspiration and skin contact. Page 282 Identify the error code and perform remedial actions on. Then, put the tank on the detergent/alcohol drawer and reconnect the tube to the cap. Close the drawer and make sure everything is secure. To shut down the system, press the power switch to turn it off, then lift the lid and dry all the tubes thoroughly before storing them in a clean area. Make sure to unplug the device from the hospital-grade power outlet. When you're printing, be careful not to touch the printer or its surroundings as they will be very hot and could cause burns. Always use the designated printer paper roll with this equipment, as using any other type may result in incorrect printing or equipment failure. To load a new printer paper roll, first make sure the power switch is turned on. Then, hold the printer cover handle and pull it towards you to access the roll holder. Insert the roll shaft through the printer paper roll and set the feed direction accordingly. Pull out about 10 cm of paper before inserting the roll between the projections. Make sure that the release lever on the left side of the printer is lowered, as this will allow the printer paper roll to be fed automatically. To close the printer cover, insert the edge of the fed paper into the slit and cut off any excess paper protruding from the slit. Before using the system, make sure to set up the disinfectant solution according to the instructions on page 236. Also, inspect and clean all parts before use by following the guidelines in Chapter 3. piping" in "Instructions-Installation Manual". Olympus recommends performing microbiological sampling of OER-Pro rinse water quality immediately after disinfecting the water supply piping if the device hasn't been used for more than 14 days. For details on rinse water
sampling, refer to Section 7.4. "Microbiological surveillance"... Page 280 If any irregularity is detected during an inspection or if the device malfunctions, do not use it. Contact Olympus for repair. Some problems may be correctable by referring to Section 8.1. "Troubleshooting guide" on page 274. If the problem cannot be resolved, do not use the device and contact Olympus. Page 281 When power is restored, drain the reprocessing basin. When using disinfectant solution and alcohol, Olympus recommends using gas filters and operating in a well-ventilated area. Wear protective gear like a face mask, gloves, and clothes to minimize aspiration and skin contact. Page 282 Identify the error code and perform remedial actions according to the instruction described in the table below. • The error code displayed on the main control panel can be cleared only by pressing the STOP/RESET button. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 283 Internal problem Contact Olympus if water supply won't stop due to high fluid level or other irregularities. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 284 Connect the drain connector to the disinfectant removal port and drain disinfectant solution from the tank. Alternatively, connect the disinfectant collection hose to the disinfectant solution nozzle and perform the "DISINFECTANT DRAIN" operation to drain disinfectant solution from the tank. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 285 Replace the air filter, purge pressure • Clogging of air filter or insufficient fluid pressure may cause issues. Clean mesh filters in the circulation port of the basin. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 286 Disinfectant Internal problem If disinfectant solution remains in the basin, perform the same remedial action as [E13]. In other cases, contact Olympus if the disinfectant equipment cannot be discharged or if water supply is insufficient. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 287 Check that cassette bottles are properly installed and not empty. If they are empty, install new ones. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 288 Section 4.8, "Installation of the printer paper roll" in the "Instructions-Installation Manual". • Release lever is raised. • Check if release lever is set in proper position. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 289 • Disinfectant solution is leaking. Check and stop using device if it leaks. Water leaks from improper installation of water filter equipment. On again. Reprocessing operator may be stopped, any reprocessing specialist feels sick during work, allergic to disinfectant, detergent or alcohol. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 291 check power supply to external devices and communication status between external devices and main device indicator on the external device is incomplete or a device malfunctioning. If problem cannot be resolved, contact control panel gas malfunctions. Olympus, ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 292 If problem cannot be resolved by remedial action described in 8.1 "Troubleshooting guide" on page 274 and need to contact Olympus, Olympus may require operation to resolve problem. In this case, perform following procedure to print information for analyzing problem and follow instruction from Olympus. Page 293 " button on subcontrol panel for 5 seconds. The printer prints information for analyzing problem. Figure 8.3 buzzer beeps and paper feed stops when printing completes. Cut printed part of paper ensure that information is printed correctly. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 294 some items may not be available in some areas. New products released after introduction of this equipment may also be compatible with this equipment. For further details, contact Olympus. If combinations of equipment other than those shown below are used, Olympus cannot guarantee that device will perform as expected. Page 295 using prefilter can extend life of water filter. 1 always use Olympus designated external devices for communication with OER-Pro. If not, Olympus cannot guarantee that device will perform as expected. For more details on external devices available in your area, contact Olympus. Page 296 I recommended value is in reference to AAMI TR134:2007 "Water for reprocessing of medical devices". Purified water has been produced through methods of either reverse osmosis (RO), deionization (DI), distillation or other methods that meet USP standards to remove impurities. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 297 refer to list of compatible endoscopes/Connecting Tubes for details) The OER-Pro does not sterilize endoscopes. Therefore, after cleaning/disinfecting an endoscope that requires sterilization, always sterilize the endoscope as instructed in its instruction manual. Numer of Max. Page 298 installation category: I No. 61010-1-2012 pollution degree: CS: 222-2 No. 61010-2-040: 2007 IEC 61011-1: 2011 IEC 61010-2-040: 2005 Radio Transmittance compliance ISO/IEC 9000-3 (Model) Center Frequency 13.56 MHz Modulation Effective Rate: 300 mw/2000 Power ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 299 - (1) 6-digit date of manufacture: (2) 7-digit serial number. 1. The OER-Pro is set for a 10-minute and 206 disinfection process for ready-to-use disinfectant solution at the factory. Program changes to the disinfection process will be released when Olympus-validated disinfectant solutions with different disinfectant contact times and temperatures are approved. Page 300 Power supply specification of this equipment is less than 220 VAC, and this fluctuations/flicker equipment is exempt from requirements of IEC 61000-3-3, emissions IEC 61000-3-3 Olympus confirmed that the level Low harmonic emissions characterize this equipment. To ensure proper operation, maintain a sufficient distance from magnetic field equipment operating with high currents (50/60 Hz). Complying with IEC 61000-4-8 and IEC 61326-2-02, it is important to note that electromagnetic interference may occur if used in an environment exceeding the maximum noise level. The device complies with part115 of the FCC rules and IC RSS210. FCC ID: SBQ-GN4215 IC: 4763B-GN4215. Modification not approved by Olympus could void the user's authority to operate the equipment. Acecide-C is safe and effective for reprocessing Olympus endoscopes and accessories, but use of unvalidated high-level disinfectants may be ineffective and damage equipment or endoscopes. Contact Olympus Technical Assistance Center at 800-848-9024 for further information. ##### Relevant Information Olympus Medical Systems Corp. reserves all rights. Reproduction or distribution without permission is prohibited. For installation and setup instructions, refer to the "Instructions - Installation Manual". OER-Pro Operation Manual: Safety Precautions and Instructions The OER-Pro Endoscope Reprocessor is designed for washing and disinfecting flexible endoscopes and their accessories using alkali detergent and an FDA-approved liquid chemical germicide. The operator must be sufficiently trained in reprocessing endoscopes to ensure safe and effective use. *Important Safety Information* Before using, thoroughly review and understand the following: • Cleaning, disinfection, and sterilization procedures described in the instruction manuals for the endoscope and ancillary equipment in well-ventilated areas when using disinfectant solution and alcohol. • Wear a face mask, gloves, and goggles to minimize aspiration and skin contact. • Equipment compatibility: Using incompatible equipment may result in patient injury and equipment malfunction. • Use this equipment in combination with ancillary equipment listed in the "System chart" in Appendix. *Care and Storage* After use, process and store the equipment according to the instructions in Chapter 5. "End-of-Day Checks", in this manual. Disposal of Waste Fluids and Equipment Guidelines Endoscope Reprocessor OER-Pro Operation Manual Chapter 2 Nomenclature and Functions 2.1 Front and Top Panel The water supply adapter provides municipal water for cleaning purposes. Connect the water supply adapter here. A built-in mesh filter is also present. ID reader section reads the user ID and scope ID. The printer displays information such as the scope ID of the reprocessed scope and the reprocessing time. 2.2 Rear Panel Buckling guard attaching holes screw holes are used to attach the buckling guard. Option terminal is used for connecting ancillary equipment (for service engineer use only). Drain hose connector has fuses. 2.3 Power cord receptacle side panel connector hanger attaching holes are provided on both left and right side panels, used to attach the optional connector hanger (MAJ-865). IDS and cleaning time refer to specific details about the EndoRapid reprocessing system, as outlined in Section 4.12 on page 95. The O-rings must be free of defects such as cracks, tears, or dents. 1. Check alcohol level and add if necessary. Check the ALCOHOL indicator on the detergent/alcohol drawer of the equipment to ensure there is sufficient alcohol present. If the alcohol level has decreased, add more as described in "Addition of Alcohol" before it reaches the "MIN" threshold. 2. Remove and replace cap and tube. - Hold the "PULL" section of the detergent/alcohol drawer and pull it out. - Detach the tube by pushing the lock lever on the connector of the tube connected to the cap on the alcohol tank and put it in a sink or other tub. 3. Fill tank with correct amount of alcohol. - Do not add alcohol while the tank is on the detergent/alcohol drawer, as this could damage the equipment. - Do not tilt the alcohol tank when there is still alcohol inside, as this may cause spills. - Pour alcohol until it is level with the line inside the tank. 4. Place tank in drawer correctly. - Ensure the ventilation tube of the alcohol tank sits on the front of the
tray, as placing it elsewhere could damage the tank. 5. Reconnect and orientate tube. - Connect the original tube to the cap. - Turn the connector to correct the tube orientation, ensuring it is not bent. 6. Inspect mesh filters. - Check that the circulation port and drain port mesh filters are not clogged. - If found clogged, clean them in running water using a brush or cotton swab. - Ensure mesh filters are properly attached in their original positions. 7. Verify disinfectant solution levels and odor. - Check the concentration of the disinfectant solution before reprocessing an endoscope, ensuring it is effective using the test strip. - Be sure to replace the disinfectant solution when its effectiveness is lost. - Wear appropriate personal protective equipment while handling the disinfectant solution. If you get solution in your eyes, immediately flush with plenty of fresh water and consult a medical professional. Page 2 ContainsENDOSCOPE REPROCESSOR OER-Pro Operation Manual Contains Labels and Symbols - Important Information Please Read Before Use Intended use Instruction manuals User qualifications Ensuring the safety of reprocessing personnel Equipment compatibility Care and Storage Maintenance and administration Repair and modification Disposal of waste fluids Disposal of this equipment Signal words Dangers warnings and cautions Terms used in these manuals Chapter 1 Checking Package Contents Chapter 2 Nomenclature and Functions 2.1 Front top panel 2.2 Rear panel 2.3 Side panel 2.5 Control panels 2.6 Consumable accessories Optional Chapter 3 Inspection Before Use 3.1 Inspecting water leakage from the water supply piping and equipment 3.2 Inspecting connecting tubes and leak test air tube 3.3 Inspecting detergent quantity and replenishment 3.5 Inspecting alcohol quantity and replenishment 3.6 Inspecting mesh filters 3.7 Inspecting power supply to external devices and communication status between external devices and main device indicator on the external device is incomplete or a device malfunctioning. If problem cannot be resolved, contact control panel gas malfunctions. Olympus, ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 292 If problem cannot be resolved by remedial action described in 8.1 "Troubleshooting guide" on page 274 and need to contact Olympus, Olympus may require operation to resolve problem. In this case, perform following procedure to print information for analyzing problem and follow instruction from Olympus. Page 293 " button on subcontrol panel for 5 seconds. The printer prints information for analyzing problem. Figure 8.3 buzzer beeps and paper feed stops when printing completes. Cut printed part of paper ensure that information is printed correctly. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 294 some items may not be available in some areas. New products released after introduction of this equipment may also be compatible with this equipment. For further details, contact Olympus. If combinations of equipment other than those shown below are used, Olympus cannot guarantee that device will perform as expected. Page 295 using prefilter can extend life of water filter. 1 always use Olympus designated external devices for communication with OER-Pro. If not, Olympus cannot guarantee that device will perform as expected. For more details on external devices available in your area, contact Olympus. Page 296 I recommended value is in reference to AAMI TR134:2007 "Water for reprocessing of medical devices". Purified water has been produced through methods of either reverse osmosis (RO), deionization (DI), distillation or other methods that meet USP standards to remove impurities. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 297 refer to list of compatible endoscopes/Connecting Tubes for details) The OER-Pro does not sterilize endoscopes. Therefore, after cleaning/disinfecting an endoscope that requires sterilization, always sterilize the endoscope as instructed in its instruction manual. Numer of Max. Page 298 installation category: I No. 61010-1-2012 pollution degree: CS: 222-2 No. 61010-2-040: 2007 IEC 61011-1: 2011 IEC 61010-2-040: 2005 Radio Transmittance compliance ISO/IEC 9000-3 (Model) Center Frequency 13.56 MHz Modulation Effective Rate: 300 mw/2000 Power ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 299 - (1) 6-digit date of manufacture: (2) 7-digit serial number. 1. The OER-Pro is set for a 10-minute and 206 disinfection process for ready-to-use disinfectant solution at the factory. Program changes to the disinfection process will be released when Olympus-validated disinfectant solutions with different disinfectant contact times and temperatures are approved. Page 300 Power supply specification of this equipment is less than 220 VAC, and this fluctuations/flicker equipment is exempt from requirements of IEC 61000-3-3, emissions IEC 61000-3-3 Olympus confirmed that the level Low harmonic emissions characterize this equipment. To ensure proper operation, maintain a sufficient distance from magnetic field equipment operating with high currents (50/60 Hz). Complying with IEC 61000-4-8 and IEC 61326-2-02, it is important to note that electromagnetic interference may occur if used in an environment exceeding the maximum noise level. The device complies with part115 of the FCC rules and IC RSS210. FCC ID: SBQ-GN4215 IC: 4763B-GN4215. Modification not approved by Olympus could void the user's authority to operate the equipment. Acecide-C is safe and effective for reprocessing Olympus endoscopes and accessories, but use of unvalidated high-level disinfectants may be ineffective and damage equipment or endoscopes. Contact Olympus Technical Assistance Center at 800-848-9024 for further information. ##### Relevant Information Olympus Medical Systems Corp. reserves all rights. Reproduction or distribution without permission is prohibited. For installation and setup instructions, refer to the "Instructions - Installation Manual". OER-Pro Operation Manual: Safety Precautions and Instructions The OER-Pro Endoscope Reprocessor is designed for washing and disinfecting flexible endoscopes and their accessories using alkali detergent and an FDA-approved liquid chemical germicide. The operator must be sufficiently trained in reprocessing endoscopes to ensure safe and effective use. *Important Safety Information* Before using, thoroughly review and understand the following: • Cleaning, disinfection, and sterilization procedures described in the instruction manuals for the endoscope and ancillary equipment in well-ventilated areas when using disinfectant solution and alcohol. • Wear a face mask, gloves, and goggles to minimize aspiration and skin contact. • Equipment compatibility: Using incompatible equipment may result in patient injury and equipment malfunction. • Use this equipment in combination with ancillary equipment listed in the "System chart" in Appendix. *Care and Storage* After use, process and store the equipment according to the instructions in Chapter 5. "End-of-Day Checks", in this manual. Disposal of Waste Fluids and Equipment Guidelines Endoscope Reprocessor OER-Pro Operation Manual Chapter 2 Nomenclature and Functions 2.1 Front and Top Panel The water supply adapter provides municipal water for cleaning purposes. Connect the water supply adapter here. A built-in mesh filter is also present. ID reader section reads the user ID and scope ID. The printer displays information such as the scope ID of the reprocessed scope and the reprocessing time. 2.2 Rear Panel Buckling guard attaching holes screw holes are used to attach the buckling guard. Option terminal is used for connecting ancillary equipment (for service engineer use only). Drain hose connector has fuses. 2.3 Power cord receptacle side panel connector hanger attaching holes are provided on both left and right side panels, used to attach the optional connector hanger (MAJ-865). IDS and cleaning time refer to specific details about the EndoRapid reprocessing system, as outlined in Section 4.12 on page 95. The O-rings must be free of defects such as cracks, tears, or dents. 1. Check alcohol level and add if necessary. Check the ALCOHOL indicator on the detergent/alcohol drawer of the equipment to ensure there is sufficient alcohol present. If the alcohol level has decreased, add more as described in "Addition of Alcohol" before it reaches the "MIN" threshold. 2. Remove and replace cap and tube. - Hold the "PULL" section of the detergent/alcohol drawer and pull it out. - Detach the tube by pushing the lock lever on the connector of the tube connected to the cap on the alcohol tank and put it in a sink or other tub. 3. Fill tank with correct amount of alcohol. - Do not add alcohol while the tank is on the detergent/alcohol drawer, as this could damage the equipment. - Do not tilt the alcohol tank when there is still alcohol inside, as this may cause spills. - Pour alcohol until it is level with the line inside the tank. 4. Place tank in drawer correctly. - Ensure the ventilation tube of the alcohol tank sits on the front of the tray, as placing it elsewhere could damage the tank. 5. Reconnect and orientate tube. - Connect the original tube to the cap. - Turn the connector to correct the tube orientation, ensuring it is not bent. 6. Inspect mesh filters. - Check that the circulation port and drain port mesh filters are not clogged. - If found clogged, clean them in running water using a brush or cotton swab. - Ensure mesh filters are properly attached in their original positions. 7. Verify disinfectant solution levels and odor. - Check the concentration of the disinfectant solution before reprocessing an endoscope, ensuring it is effective using the test strip. - Be sure to replace the disinfectant solution when its effectiveness is lost. - Wear appropriate personal protective equipment while handling the disinfectant solution. If you get solution in your eyes, immediately flush with plenty of
fresh water and consult a medical professional. Page 2 ContainsENDOSCOPE REPROCESSOR OER-Pro Operation Manual Contains Labels and Symbols - Important Information Please Read Before Use Intended use Instruction manuals User qualifications Ensuring the safety of reprocessing personnel Equipment compatibility Care and Storage Maintenance and administration Repair and modification Disposal of waste fluids Disposal of this equipment Signal words Dangers warnings and cautions Terms used in these manuals Chapter 1 Checking Package Contents Chapter 2 Nomenclature and Functions 2.1 Front top panel 2.2 Rear panel 2.3 Side panel 2.5 Control panels 2.6 Consumable accessories Optional Chapter 3 Inspection Before Use 3.1 Inspecting water leakage from the water supply piping and equipment 3.2 Inspecting connecting tubes and leak test air tube 3.3 Inspecting detergent quantity and replenishment 3.5 Inspecting alcohol quantity and replenishment 3.6 Inspecting mesh filters 3.7 Inspecting power supply to external devices and communication status between external devices and main device indicator on the external device is incomplete or a device malfunctioning. If problem cannot be resolved, contact control panel gas malfunctions. Olympus, ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 292 If problem cannot be resolved by remedial action described in 8.1 "Troubleshooting guide" on page 274 and need to contact Olympus, Olympus may require operation to resolve problem. In this case, perform following procedure to print information for analyzing problem and follow instruction from Olympus. Page 293 " button on subcontrol panel for 5 seconds. The printer prints information for analyzing problem. Figure 8.3 buzzer beeps and paper feed stops when printing completes. Cut printed part of paper ensure that information is printed correctly. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 294 some items may not be available in some areas. New products released after introduction of this equipment may also be compatible with this equipment. For further details, contact Olympus. If combinations of equipment other than those shown below are used, Olympus cannot guarantee that device will perform as expected. Page 295 using prefilter can extend life of water filter. 1 always use Olympus designated external devices for communication with OER-Pro. If not, Olympus cannot guarantee that device will perform as expected. For more details on external devices available in your area, contact Olympus. Page 296 I recommended value is in reference to AAMI TR134:2007 "Water for reprocessing of medical devices". Purified water has been produced through methods of either reverse osmosis (RO), deionization (DI), distillation or other methods that meet USP standards to remove impurities. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 297 refer to list of compatible endoscopes/Connecting Tubes for details) The OER-Pro does not sterilize endoscopes. Therefore, after cleaning/disinfecting an endoscope that requires sterilization, always sterilize the endoscope as instructed in its instruction manual. Numer of Max. Page 298 installation category: I No. 61010-1-2012 pollution degree: CS: 222-2 No. 61010-2-040: 2007 IEC 61011-1: 2011 IEC 61010-2-040: 2005 Radio Transmittance compliance ISO/IEC 9000-3 (Model) Center Frequency 13.56 MHz Modulation Effective Rate: 300 mw/2000 Power ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 299 - (1) 6-digit date of manufacture: (2) 7-digit serial number. 1. The OER-Pro is set for a 10-minute and 206 disinfection process for ready-to-use disinfectant solution at the factory. Program changes to the disinfection process will be released when Olympus-validated disinfectant solutions with different disinfectant contact times and temperatures are approved. Page 300 Power supply specification of this equipment is less than 220 VAC, and this fluctuations/flicker equipment is exempt from requirements of IEC 61000-3-3, emissions IEC 61000-3-3 Olympus confirmed that the level Low harmonic emissions characterize this equipment. To ensure proper operation, maintain a sufficient distance from magnetic field equipment operating with high currents (50/60 Hz). Complying with IEC 61000-4-8 and IEC 61326-2-02, it is important to note that electromagnetic interference may occur if used in an environment exceeding the maximum noise level. The device complies with part115 of the FCC rules and IC RSS210. FCC ID: SBQ-GN4215 IC: 4763B-GN4215. Modification not approved by Olympus could void the user's authority to operate the equipment. Acecide-C is safe and effective for reprocessing Olympus endoscopes and accessories, but use of unvalidated high-level disinfectants may be ineffective and damage equipment or endoscopes. Contact Olympus Technical Assistance Center at 800-848-9024 for further information. ##### Relevant Information Olympus Medical Systems Corp. reserves all rights. Reproduction or distribution without permission is prohibited. For installation and setup instructions, refer to the "Instructions - Installation Manual". OER-Pro Operation Manual: Safety Precautions and Instructions The OER-Pro Endoscope Reprocessor is designed for washing and disinfecting flexible endoscopes and their accessories using alkali detergent and an FDA-approved liquid chemical germicide. The operator must be sufficiently trained in reprocessing endoscopes to ensure safe and effective use. *Important Safety Information* Before using, thoroughly review and understand the following: • Cleaning, disinfection, and sterilization procedures described in the instruction manuals for the endoscope and ancillary equipment in well-ventilated areas when using disinfectant solution and alcohol. • Wear a face mask, gloves, and goggles to minimize aspiration and skin contact. • Equipment compatibility: Using incompatible equipment may result in patient injury and equipment malfunction. • Use this equipment in combination with ancillary equipment listed in the "System chart" in Appendix. *Care and Storage* After use, process and store the equipment according to the instructions in Chapter 5. "End-of-Day Checks", in this manual. Disposal of Waste Fluids and Equipment Guidelines Endoscope Reprocessor OER-Pro Operation Manual Chapter 2 Nomenclature and Functions 2.1 Front and Top Panel The water supply adapter provides municipal water for cleaning purposes. Connect the water supply adapter here. A built-in mesh filter is also present. ID reader section reads the user ID and scope ID. The printer displays information such as the scope ID of the reprocessed scope and the reprocessing time. 2.2 Rear Panel Buckling guard attaching holes screw holes are used to attach the buckling guard. Option terminal is used for connecting ancillary equipment (for service engineer use only). Drain hose connector has fuses. 2.3 Power cord receptacle side panel connector hanger attaching holes are provided on both left and right side panels, used to attach the optional connector hanger (MAJ-865). IDS and cleaning time refer to specific details about the EndoRapid reprocessing system, as outlined in Section 4.12 on page 95. The O-rings must be free of defects such as cracks, tears, or dents. 1. Check alcohol level and add if necessary. Check the ALCOHOL indicator on the detergent/alcohol drawer of the equipment to ensure there is sufficient alcohol present. If the alcohol level has decreased, add more as described in "Addition of Alcohol" before it reaches the "MIN" threshold. 2. Remove and replace cap and tube. - Hold the "PULL" section of the detergent/alcohol drawer and pull it out. - Detach the tube by pushing the lock lever on the connector of the tube connected to the cap on the alcohol tank and put it in a sink or other tub. 3. Fill tank with correct amount of alcohol. - Do not add alcohol while the tank is on the detergent/alcohol drawer, as this could damage the equipment. - Do not tilt the alcohol tank when there is still alcohol inside, as this may cause spills. - Pour alcohol until it is level with the line inside the tank. 4. Place tank in drawer correctly. - Ensure the ventilation tube of the alcohol tank sits on the front of the tray, as placing it elsewhere could damage the tank. 5. Reconnect and orientate tube. - Connect the original tube to the cap. - Turn the connector to correct the tube orientation, ensuring it is not bent. 6. Inspect mesh filters. - Check that the circulation port and drain port mesh filters are not clogged. - If found clogged, clean them in running water using a brush or cotton swab. - Ensure mesh filters are properly attached in their original positions. 7. Verify disinfectant solution levels and odor. - Check the concentration of the disinfectant solution before reprocessing an endoscope, ensuring it is effective using the test strip. - Be sure to replace the disinfectant solution when its effectiveness is lost. - Wear appropriate personal protective equipment while handling the disinfectant solution. If you get solution in your eyes, immediately flush with plenty of fresh water and consult a medical professional. Page 2 ContainsENDOSCOPE REPROCESSOR OER-Pro Operation Manual Contains Labels and Symbols - Important Information Please Read Before Use Intended use Instruction manuals User qualifications Ensuring the safety of reprocessing personnel Equipment compatibility Care and Storage Maintenance and administration Repair and modification Disposal of waste fluids Disposal of this equipment Signal words Dangers warnings and cautions Terms used in these manuals Chapter 1 Checking Package Contents Chapter 2 Nomenclature and Functions 2.1 Front top panel 2.2 Rear panel 2.3 Side panel 2.5 Control panels 2.6 Consumable accessories Optional Chapter 3 Inspection Before Use 3.1 Inspecting water leakage from the water supply piping and equipment 3.2 Inspecting connecting tubes and leak test air tube 3.3 Inspecting detergent quantity and
replenishment 3.5 Inspecting alcohol quantity and replenishment 3.6 Inspecting mesh filters 3.7 Inspecting power supply to external devices and communication status between external devices and main device indicator on the external device is incomplete or a device malfunctioning. If problem cannot be resolved, contact control panel gas malfunctions. Olympus, ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 292 If problem cannot be resolved by remedial action described in 8.1 "Troubleshooting guide" on page 274 and need to contact Olympus, Olympus may require operation to resolve problem. In this case, perform following procedure to print information for analyzing problem and follow instruction from Olympus. Page 293 " button on subcontrol panel for 5 seconds. The printer prints information for analyzing problem. Figure 8.3 buzzer beeps and paper feed stops when printing completes. Cut printed part of paper ensure that information is printed correctly. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 294 some items may not be available in some areas. New products released after introduction of this equipment may also be compatible with this equipment. For further details, contact Olympus. If combinations of equipment other than those shown below are used, Olympus cannot guarantee that device will perform as expected. Page 295 using prefilter can extend life of water filter. 1 always use Olympus designated external devices for communication with OER-Pro. If not, Olympus cannot guarantee that device will perform as expected. For more details on external devices available in your area, contact Olympus. Page 296 I recommended value is in reference to AAMI TR134:2007 "Water for reprocessing of medical devices". Purified water has been produced through methods of either reverse osmosis (RO), deionization (DI), distillation or other methods that meet USP standards to remove impurities. ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 297 refer to list of compatible endoscopes/Connecting Tubes for details) The OER-Pro does not sterilize endoscopes. Therefore, after cleaning/disinfecting an endoscope that requires sterilization, always sterilize the endoscope as instructed in its instruction manual. Numer of Max. Page 298 installation category: I No. 61010-1-2012 pollution degree: CS: 222-2 No. 61010-2-040: 2007 IEC 61011-1: 2011 IEC 61010-2-040: 2005 Radio Transmittance compliance ISO/IEC 9000-3 (Model) Center Frequency 13.56 MHz Modulation Effective Rate: 300 mw/2000 Power ENDOSCOPE REPROCESSOR OER-Pro Operation Manual... Page 299 - (1) 6-digit date of manufacture: (2) 7-digit serial number. 1. The OER-Pro is set for a 10-minute and 206 disinfection process for ready-to-use disinfectant solution at the factory. Program changes to the disinfection process will be released when Olympus-validated disinfectant solutions with different disinfectant contact times and temperatures are approved. Page 300 Power supply specification of this equipment is less than 220 VAC, and this fluctuations/flicker equipment is exempt from requirements of IEC 61000-3-3, emissions IEC 61000-3-3 Olympus confirmed that the level Low harmonic emissions characterize this equipment. To ensure proper operation, maintain a sufficient distance from magnetic field equipment operating with high currents (50/60 Hz). Complying with IEC 61000-4-8 and IEC 61326-2-02, it is important to note that electromagnetic interference may occur if used in an environment exceeding the maximum noise level. The device complies with part115 of the FCC rules and IC RSS210. FCC ID: SBQ-GN421 |

button stops a process or clears any error codes. START button begins the selected program. The Endoscope Reprocessor OER-Pro Operation Manual The endoscope reprocessor OER-Pro has several features to ensure proper operation. The device includes an automatic operation that can be activated independently, and air purge is used to drain cleaning fluid or disinfectant solution from the equipment when necessary. Additionally, safety-related labels and symbols are attached to the equipment for reference. The rear panel of the reprocessor includes a terminal for connecting ancillary equipment, which should only be used by authorized service engineers. The front panel features an RFID marking, while the top panel displays important information such as the rotation direction indicator label and rating plate with product model, power rating, and serial number. Before using the reprocessor, it is essential to review the instructions carefully, including the installation manual and operation manual. These manuals provide critical information for safe and effective use of the equipment. User qualifications to operate Endoscope Reprocessor OER-Pro must be thoroughly trained in reprocessing endoscopes. Infection cases have been reported due to improper cleaning, disinfection, and sterilization. Review and understand the following guidelines before use: cleaning procedures for endoscopes and ancillary equipment, professional health and safety standards, guidelines on cleaning and disinfection of endoscopy equipment, structure and handling of endoscopic equipment, and personal protective equipment requirements. Additional information: Before using high-level disinfectant solution, carefully read instructions and material safety data sheet. Wear appropriate personal protective equipment to prevent contact with or inhalation of infectious substances or disinfectant. Refer to guidelines from associations such as SGNA, ASGE, APIC, AORN, ASTM, OSHA, ACGIH, NIOSH, and AIA for ventilation requirements.