

Continue



Last Updated on February 11, 2025 by Alan Weir As an expert car locksmith, I often encounter clients frustrated by their car immobiliser systems. If you've ever found yourself stranded in a car park starting in disbelief at your cars dashboard because it wont start, youre not alone. The immobiliser is a crucial safety feature; however, it can be a bit of a headache if it malfunctions. No need to worry, though! In this guide, Ill walk you through how to reset your cars immobiliser system, ensuring youre back on the road swiftly and safely. Understanding the Immobiliser System Before we dive into the reset process, its important to grasp what an immobiliser is and how it works. Essentially, an immobiliser is an electronic security device fitted within your vehicle. Its primary role is to prevent the engine from starting without the correct key or key fob. When your key sends a signal to the cars engine control unit (ECU), it verifies that the key is legitimate. If its not, the engine wont start/simply prevention of theft! When immobilisers malfunction, they can cause various issues, including difficulties in starting your car, lights on the dashboard signalling an alarm, or worse, leaving you stranded. When Do You Need to Reset the Immobiliser? You may need to reset your immobiliser if: Youve replaced the battery in your key fob. Your key fob is damaged or waterlogged. Youve recently had maintenance or repairs that affected the electrical systems in your car. Understandably, dealing with a vehicle that wont start can be exasperating, but resetting your immobiliser might just do the trick. So, lets get started! Step-by-Step Guide: How to Reset Your Cars Immobiliser Step 1: Gather Your Key and Essentials First and foremost, ensure you have your key or key fob handy. This is critical for triggering the immobiliser system. You may also want to have a pen and paper on hand to jot down any findings or codes if your dashboard gives you any error messages. Step 2: Check the Battery A common issue with immobilisers is weak key fob batteries. Before diving into the reset process, check your keys battery. If its low, replace it with a new one. Many modern fobs use CR2032 batteries, which are widely available at local shops or online. For a quick guide on replacing the battery, you can refer to this helpful resource on YouTube. Step 3: Locate the OBD-II Port Your next step is to find the OBD-II (On-Board Diagnostics) port, usually located under the dashboard to the left of the steering wheel. This port is where mechanics plug in diagnostic tools to communicate with your vehicles ECU. In some cars, it might even be located in the centre console or near the drivers seat. If youre unsure about its position, there are handy resources available that offer visual guides. Step 4: Connecting the Diagnostic Tool To reset the immobiliser, youll typically need an OBD-II scanner. If you dont own one, many local garages lend them, or you can purchase an affordable model online. Once you have the tool ready, plug it into the OBD-II port. Most tools will automatically power on when connected. Step 5: Ignition On/Your vehicles ignition on without starting the engine. This is usually done by turning the key to the "On" position, but without cranking the engine. Your dashboard lights should illuminate, indicating that the power is on. Step 6: Access the Immobiliser Settings Depending on the device your layout may vary, but youll be looking for options labeled Security or Immobiliser. If youre unsure about specifics, many scanners come with user manuals, and you may also find useful walkthroughs online. Step 7: Follow the On-Screen Prompts Once youve accessed the immobiliser section, there should be an option to reset clear fault codes. Select the reset option, following the prompts carefully. This process usually takes just a few seconds. When completed, you should receive a confirmation message on the scanner. Step 8: Test the Key After you reset the system, its time to test your key. Turn off the ignition, remove the key from the ignition, and then insert it again. Attempt to start your vehicle. If the reset was successful, your car should fire right up without issues. Alternative Reset Methods Sometimes, your vehicle may have its own specific reset methods. For many manufacturers, there are unique procedures that can vary from one model to another. Here are some general alternatives that might work for you: Lock and Unlock the Doors: Some vehicles allow you to reset the immobiliser by locking and unlocking the door with the key fob multiple times. Each manufacturer has its own set of rules, so be sure to consult your owners manual for details.Battery Disconnect: Disconnecting your car battery for about 15 minutes can also trigger a reset in certain systems. However, be cautious with this method, as it may reset other electronic settings in your vehicle like radio presets. Manuals and Online Forums: If your car belongs to a more obscure model or brand, checking the owners manual or joining online forums specific to that make can provide targeted advice and community support. These resources often have members whove encountered the same issue and can offer tried and tested solutions. When Professional Help Is Necessary Resetting your immobiliser yourself is a feasible task with a little patience and the right tools. However, if after following all these steps your vehicle still refuses to cooperate, its time to seek professional help. A certified mechanic or locksmith can accurately diagnose the problem using advanced equipment, ensuring that any underlying issues are addressed. Important Safety Reminders Always Take Precautions If youre working on your cars electrical system, make sure you are grounded to avoid any shocks or burns. Consult Your Owners Manual: Each vehicle is different, and often the manufacturers provides specific guidance regarding the immobiliser system. Your manual may hold hidden gems that can save you time. Dont Hesitate to Get Help: Never feel ashamed to call in the pros if youre unsure or uncomfortable with any step in the process. Its always better to be safe than sorry. Stay Vigilant Lastly, an immobiliser reset can often be a temporary fix. If you find recurring issues, it might indicate a deeper problem with your key fob or the immobiliser system itself. Regular check-ups or diagnostics can prevent sudden vehicular failures and ensure your peace of mind on the road. By understanding the immobiliser system and following these steps, youll not only empower yourself but also enhance your approach to vehicle maintenance. Now go ahead, give that reset a try, and soon enough youll be cruising again! Alan Weir If you need to reset your security anti-theft system, there are a few steps you can follow to do so. This process can help you regain access to your vehicle or property if you've lost your keys or the system has been activated unexpectedly. Resetting the Anti-Theft System To reset your security anti-theft system, follow these steps: Locate the anti-theft system control module, which is usually found under the dashboard or in the engine compartment. Disconnect the negative battery cable from the vehicle's battery for at least 30 seconds. This will reset the system's memory and clear any existing codes or settings. Reconnect the negative battery cable and turn on the ignition. The anti-theft system should now be reset and ready for you to program new keys or access codes.If you're still having trouble with the anti-theft system after resetting it, you may need to consult your owner's manual or contact the manufacturer for further assistance.Importance of Resetting the Anti-Theft SystemResetting your security anti-theft system is important for a few key reasons:Regain Access: If you've lost your keys or the system has been activated unexpectedly, resetting the system can help you regain access to your vehicle or property. Clear Fault Codes: Sometimes, the system may store fault codes that prevent it from working properly. Resetting the system can clear these codes and allow the system to function normally again. Enhance Security: Resetting the system can also help you program new keys or access codes, ensuring that only authorized users can start the vehicle. Follow the Steps: The steps provided above are general guidelines. The specific steps may vary depending on the vehicle's make and model. It's important to consult your owner's manual or a professional for more detailed instructions. If you're unsure about any step, it's best to seek professional assistance. Resetting the Anti-Theft System Step 1: Disconnect the Battery. Locate the car's battery and use the appropriate tools to disconnect the negative terminal.Step 2: Wait for 30 Minutes.Step 3: Reconnect the Battery.Step 4: Start the Car.The anti-theft fuse is typically in the fuse box on the driver's side. Depending on the vehicle's specifications, the anti-theft fuse can also be found under the hood and behind the air filter. You can use a fuse puller or a pair of pliers to disable the alarm.Method 3: Insert the key into your car's doorStep 1: Insert the key into the door lock.Step 2: Turn the vehicle key to unlock the car door without releasing it.Step 3: Try starting the engine. Need to reset the security light in your car? If the security light is blinking the immobilizer system is enabled and will not allow the car to start. What Goes Wrong? Most cars today have a security system built into the electrical system (BCM - Body control module) to deter from theft. The problem is it can sometimes stop the person that owns the car from starting the engine as well. These anti-theft systems can sometimes get the operational sequence out of sync which makes the system think the car is getting stolen epically after a repair job. This can sometimes happen when there is no one in the car but the window is rolled down while the car is locked. Someone will reach their hand inside and unlock any of the doors. Another common way for the system becoming triggered is to simply disconnect the battery to install a new unit, or if the battery is allowed to go dead and then jump started. These can sometimes cause an electrical surge triggering the immobilizer system. How Does it Work? Car alarms are designed to prevent burglary of the car and warn the owner if a burglar enters the car. The alarm is activated by a sensor that detects motion or vibration. When the alarm is activated, the siren will sound and the lights will flash. The alarm can be reset by turning the key in the ignition and then turning the key to the "On" position. If the alarm is still sounding after a few minutes, you may need to disconnect the battery and then reconnect it. Some cars have alarm systems which send out SOS signals to a cell phone number in case of breakdown or theft. Alarm systems are also incorporated within a navigation system to increase the security of the car, the navigation system will send out a ping signal so the car can be received. The security system can also be used to locate the car in large parking lots by using the conformation chirp on the remote fob. Sometimes a car alarm can give out a false alarm when it feels vibrations of thunder or a passing truck. Sensors need to be adjusted properly otherwise it can trigger the device even when a person accidentally touches the automobile as well. Security systems utilize a remote controller (key fob) so a user can disable the alarm from a distance. The remote control feature is very convenient if the system is triggered by a false alarm. A key fob can integrate a variety of functions such as a LCD screen option which can project the image of a part of a vehicle that is under threat by a thief is one example. Can I Bypass My Car Alarm? A simple response to this question is no most cases no. Security systems are designed through the main PCM and BCM which control a major part of the vehicle's operating system. Until this system is enabled many systems such as fuel and ignition are shut down. What We Did We called name brand dealerships and told the service writer, (who sometimes got us a technician) a car we bought from them is in the parking lot with a mom waiting to pick up her kids from school with the alarm light flashing and the car wont start, this worked pretty well. We have noted down their responses. Hopefully you can gather enough information from us and them to get your car going again. (We have noticed popular similarities in almost all cars which are pretty generic which we have listed below. Security Reset Instructions This is a generic alarm immobilizer reset procedure and it applies to most vehicles. Step 1: Drivers Door Key Reset Exit the car with all doors closed and the windows rolled up. Also, close and any rear doors such as the trunk, hatch or tailgate and the car door. Turn the key in the ignition and then turn the key to the "On" position. Wait for 10 seconds. Step 2: Turn the key to the "Off" position. Wait for 10 seconds. Step 3: Turn the key to the "On" position. Wait for 10 seconds. Step 4: Turn the key to the "Off" position. Wait for 10 seconds. Step 5: Turn the key to the "On" position. Wait for 10 seconds. Step 6: Turn the key to the "Off" position. Wait for 10 seconds. Step 7: Turn the key to the "On" position. Wait for 10 seconds. Step 8: Turn the key to the "Off" position. Wait for 10 seconds. Step 9: Turn the key to the "On" position. Wait for 10 seconds. Step 10: Turn the key to the "Off" position. Wait for 10 seconds. Step 11: Turn the key to the "On" position. Wait for 10 seconds. Step 12: Turn the key to the "Off" position. Wait for 10 seconds. Step 13: Turn the key to the "On" position. Wait for 10 seconds. Step 14: Turn the key to the "Off" position. Wait for 10 seconds. Step 15: Turn the key to the "On" position. Wait for 10 seconds. Step 16: Turn the key to the "Off" position. Wait for 10 seconds. Step 17: Turn the key to the "On" position. Wait for 10 seconds. Step 18: Turn the key to the "Off" position. Wait for 10 seconds. Step 19: Turn the key to the "On" position. Wait for 10 seconds. Step 20: Turn the key to the "Off" position. Wait for 10 seconds. Step 21: Turn the key to the "On" position. Wait for 10 seconds. Step 22: Turn the key to the "Off" position. Wait for 10 seconds. Step 23: Turn the key to the "On" position. Wait for 10 seconds. Step 24: Turn the key to the "Off" position. Wait for 10 seconds. Step 25: Turn the key to the "On" position. Wait for 10 seconds. Step 26: Turn the key to the "Off" position. Wait for 10 seconds. Step 27: Turn the key to the "On" position. Wait for 10 seconds. Step 28: Turn the key to the "Off" position. Wait for 10 seconds. Step 29: Turn the key to the "On" position. Wait for 10 seconds. Step 30: Turn the key to the "Off" position. Wait for 10 seconds. Step 31: Turn the key to the "On" position. Wait for 10 seconds. Step 32: Turn the key to the "Off" position. Wait for 10 seconds. Step 33: Turn the key to the "On" position. Wait for 10 seconds. Step 34: Turn the key to the "Off" position. Wait for 10 seconds. Step 35: Turn the key to the "On" position. Wait for 10 seconds. Step 36: Turn the key to the "Off" position. Wait for 10 seconds. Step 37: Turn the key to the "On" position. Wait for 10 seconds. Step 38: Turn the key to the "Off" position. Wait for 10 seconds. Step 39: Turn the key to the "On" position. Wait for 10 seconds. Step 40: Turn the key to the "Off" position. Wait for 10 seconds. Step 41: Turn the key to the "On" position. Wait for 10 seconds. Step 42: Turn the key to the "Off" position. Wait for 10 seconds. Step 43: Turn the key to the "On" position. Wait for 10 seconds. Step 44: Turn the key to the "Off" position. Wait for 10 seconds. Step 45: Turn the key to the "On" position. Wait for 10 seconds. Step 46: Turn the key to the "Off" position. Wait for 10 seconds. Step 47: Turn the key to the "On" position. Wait for 10 seconds. Step 48: Turn the key to the "Off" position. Wait for 10 seconds. Step 49: Turn the key to the "On" position. Wait for 10 seconds. Step 50: Turn the key to the "Off" position. Wait for 10 seconds. Step 51: Turn the key to the "On" position. Wait for 10 seconds. Step 52: Turn the key to the "Off" position. Wait for 10 seconds. Step 53: Turn the key to the "On" position. Wait for 10 seconds. Step 54: Turn the key to the "Off" position. Wait for 10 seconds. Step 55: Turn the key to the "On" position. Wait for 10 seconds. Step 56: Turn the key to the "Off" position. Wait for 10 seconds. Step 57: Turn the key to the "On" position. Wait for 10 seconds. Step 58: Turn the key to the "Off" position. Wait for 10 seconds. Step 59: Turn the key to the "On" position. Wait for 10 seconds. Step 60: Turn the key to the "Off" position. Wait for 10 seconds. Step 61: Turn the key to the "On" position. Wait for 10 seconds. Step 62: Turn the key to the "Off" position. Wait for 10 seconds. Step 63: Turn the key to the "On" position. Wait for 10 seconds. Step 64: Turn the key to the "Off" position. Wait for 10 seconds. Step 65: Turn the key to the "On" position. Wait for 10 seconds. Step 66: Turn the key to the "Off" position. Wait for 10 seconds. Step 67: Turn the key to the "On" position. Wait for 10 seconds. Step 68: Turn the key to the "Off" position. Wait for 10 seconds. Step 69: Turn the key to the "On" position. Wait for 10 seconds. Step 70: Turn the key to the "Off" position. Wait for 10 seconds. Step 71: Turn the key to the "On" position. Wait for 10 seconds. Step 72: Turn the key to the "Off" position. Wait for 10 seconds. Step 73: Turn the key to the "On" position. Wait for 10 seconds. Step 74: Turn the key to the "Off" position. Wait for 10 seconds. Step 75: Turn the key to the "On" position. Wait for 10 seconds. Step 76: Turn the key to the "Off" position. Wait for 10 seconds. Step 77: Turn the key to the "On" position. Wait for 10 seconds. Step 78: Turn the key to the "Off" position. Wait for 10 seconds. Step 79: Turn the key to the "On" position. Wait for 10 seconds. Step 80: Turn the key to the "Off" position. Wait for 10 seconds. Step 81: Turn the key to the "On" position. Wait for 10 seconds. Step 82: Turn the key to the "Off" position. Wait for 10 seconds. Step 83: Turn the key to the "On" position. Wait for 10 seconds. Step 84: Turn the key to the "Off" position. Wait for 10 seconds. Step 85: Turn the key to the "On" position. Wait for 10 seconds. Step 86: Turn the key to the "Off" position. Wait for 10 seconds. Step 87: Turn the key to the "On" position. Wait for 10 seconds. Step 88: Turn the key to the "Off" position. Wait for 10 seconds. Step 89: Turn the key to the "On" position. Wait for 10 seconds. Step 90: Turn the key to the "Off" position. Wait for 10 seconds. Step 91: Turn the key to the "On" position. Wait for 10 seconds. Step 92: Turn the key to the "Off" position. Wait for 10 seconds. Step 93: Turn the key to the "On" position. Wait for 10 seconds. Step 94: Turn the key to the "Off" position. Wait for 10 seconds. Step 95: Turn the key to the "On" position. Wait for 10 seconds. Step 96: Turn the key to the "Off" position. Wait for 10 seconds. Step 97: Turn the key to the "On" position. Wait for 10 seconds. Step 98: Turn the key to the "Off" position. Wait for 10 seconds. Step 99: Turn the key to the "On" position. Wait for 10 seconds. Step 100: Turn the key to the "Off" position. Wait for 10 seconds. Step 101: Turn the key to the "On" position. Wait for 10 seconds. Step 102: Turn the key to the "Off" position. Wait for 10 seconds. Step 103: Turn the key to the "On" position. Wait for 10 seconds. Step 104: Turn the key to the "Off" position. Wait for 10 seconds. Step 105: Turn the key to the "On" position. Wait for 10 seconds. Step 106: Turn the key to the "Off" position. Wait for 10 seconds. Step 107: Turn the key to the "On" position. Wait for 10 seconds. Step 108: Turn the key to the "Off" position. Wait for 10 seconds. Step 109: Turn the key to the "On" position. Wait for 10 seconds. Step 110: Turn the key to the "Off" position. Wait for 10 seconds. Step 111: Turn the key to the "On" position. Wait for 10 seconds. Step 112: Turn the key to the "Off" position. Wait for 10 seconds. Step 113: Turn the key to the "On" position. Wait for 10 seconds. Step 114: Turn the key to the "Off" position. Wait for 10 seconds. Step 115: Turn the key to the "On" position. Wait for 10 seconds. Step 116: Turn the key to the "Off" position. Wait for 10 seconds. Step 117: Turn the key to the "On" position. Wait for 10 seconds. Step 118: Turn the key to the "Off" position. Wait for 10 seconds. Step 119: Turn the key to the "On" position. Wait for 10 seconds. Step 120: Turn the key to the "Off" position. Wait for 10 seconds. Step 121: Turn the key to the "On" position. Wait for 10 seconds. Step 122: Turn the key to the "Off" position. Wait for 10 seconds. Step 123: Turn the key to the "On" position. Wait for 10 seconds. Step 124: Turn the key to the "Off" position. Wait for 10 seconds. Step 125: Turn the key to the "On" position. Wait for 10 seconds. Step 126: Turn the key to the "Off" position. Wait for 10 seconds. Step 127: Turn the key to the "On" position. Wait for 10 seconds. Step 128: Turn the key to the "Off" position. Wait for 10 seconds. Step 129: Turn the key to the "On" position. Wait for 10 seconds. Step 130: Turn the key to the "Off" position. Wait for 10 seconds. Step 131: Turn the key to the "On" position. Wait for 10 seconds. Step 132: Turn the key to the "Off" position. Wait for 10 seconds. Step 133: Turn the key to the "On" position. Wait for 10 seconds. Step 134: Turn the key to the "Off" position. Wait for 10 seconds. Step 135: Turn the key to the "On" position. Wait for 10 seconds. Step 136: Turn the key to the "Off" position. Wait for 10 seconds. Step 137: Turn the key to the "On" position. Wait for 10 seconds. Step 138: Turn the key to the "Off" position. Wait for 10 seconds. Step 139: Turn the key to the "On" position. Wait for 10 seconds. Step 140: Turn the key to the "Off" position. Wait for 10 seconds. Step 141: Turn the key to the "On" position. Wait for 10 seconds. Step 142: Turn the key to the "Off" position. Wait for 10 seconds. Step 143: Turn the key to the "On" position. Wait for 10 seconds. Step 144: Turn the key to the "Off" position. Wait for 10 seconds. Step 145: Turn the key to the "On" position. Wait for 10 seconds. Step 146: Turn the key to the "Off" position. Wait for 10 seconds. Step 147: Turn the key to the "On" position. Wait for 10 seconds. Step 148: Turn the key to the "Off" position. Wait for 10 seconds. Step 149: Turn the key to the "On" position. Wait for 10 seconds. Step 150: Turn the key to the "Off" position. Wait for 10 seconds. Step 151: Turn the key to the "On" position. Wait for 10 seconds. Step 152: Turn the key to the "Off" position. Wait for 10 seconds. Step 153: Turn the key to the "On" position. Wait for 10 seconds. Step 154: Turn the key to the "Off" position. Wait for 10 seconds. Step 155: Turn the key to the "On" position. Wait for 10 seconds. Step 156: Turn the key to the "Off" position. Wait for 10 seconds. Step 157: Turn the key to the "On" position. Wait for 10 seconds. Step 158: Turn the key to the "Off" position. Wait for 10 seconds. Step 159: Turn the key to the "On" position. Wait for 10 seconds. Step 160: Turn the key to the "Off" position. Wait for 10 seconds. Step 161: Turn the key to the "On" position. Wait for 10 seconds. Step 162: Turn the key to the "Off" position. Wait for 10 seconds. Step 163: Turn the key to the "On" position. Wait for 10 seconds. Step 164: Turn the key to the "Off" position. Wait for 10 seconds. Step 165: Turn the key to the "On" position. Wait for 10 seconds. Step 166: Turn the key to the "Off" position. Wait for 10 seconds. Step 167: Turn the key to the "On" position. Wait for 10 seconds. Step 168: Turn the key to the "Off" position. Wait for 10 seconds. Step 169: Turn the key to the "On" position. Wait for 10 seconds. Step 170: Turn the key to the "Off" position. Wait for 10 seconds. Step 171: Turn the key to the "On" position. Wait for 10 seconds. Step 172: Turn the key to the "Off" position. Wait for 10 seconds. Step 173: Turn the key to the "On" position. Wait for 10 seconds. Step 174: Turn the key to the "Off" position. Wait for 10 seconds. Step 175: Turn the key to the "On" position. Wait for 10 seconds. Step 176: Turn the key to the "Off" position. Wait for 10 seconds. Step 177: Turn the key to the "On" position. Wait for 10 seconds. Step 178: Turn the key to the "Off" position. Wait for 10 seconds. Step 179: Turn the key to the "On" position. Wait for 10 seconds. Step 180: Turn the key to the "Off" position. Wait for 10 seconds. Step 181: Turn the key to the "On" position. Wait for 10 seconds. Step 182: Turn the key to the "Off" position. Wait for 10 seconds. Step 183: Turn the key to the "On" position. Wait for 10 seconds. Step 184: Turn the key to the "Off" position. Wait for 10 seconds. Step 185: Turn the key to the "On" position. Wait for 10 seconds. Step 186: Turn the key to the "Off" position. Wait for 10 seconds. Step 187: Turn the key to the "On" position. Wait for 10 seconds. Step 188: Turn the key to the "Off" position. Wait for 10 seconds. Step 189: Turn the key to the "On" position. Wait for 10 seconds. Step 190: Turn the key to the "Off" position. Wait for 10 seconds. Step 191: Turn the key to the "On" position. Wait for 10 seconds. Step 192: Turn the key to the "Off" position. Wait for 10 seconds. Step 193: Turn the key to the "On" position. Wait for 10 seconds. Step 194: Turn the key to the "Off" position. Wait for 10 seconds. Step 195: Turn the key to the "On" position. Wait for 10 seconds. Step 196: Turn the key to the "Off" position. Wait for 10 seconds. Step 197: Turn the key to the "On" position. Wait for 10 seconds. Step 198: Turn the key to the "Off" position. Wait for 10 seconds. Step 199: Turn the key to the "On" position. Wait for 10 seconds. Step 200: Turn the key to the "Off" position. Wait for 10 seconds. Step 201: Turn the key to the "On" position. Wait for 10 seconds. Step 202: Turn the key to the "Off" position. Wait for 10 seconds. Step 203: Turn the key to the "On" position. Wait for 10 seconds. Step 204: Turn the key to the "Off" position. Wait for 10 seconds. Step 205: Turn the key to the "On" position. Wait for 10 seconds. Step 206: Turn the key to the "Off" position. Wait for 10 seconds. Step 207: Turn the key to the "On" position. Wait for 10 seconds. Step 208: Turn the key to the "Off" position. Wait for 10 seconds. Step 209: Turn the key to the "On" position. Wait for 10 seconds. Step 210: Turn the key to the "Off" position. Wait for 10 seconds. Step 211: Turn the key to the "On" position. Wait for 10 seconds. Step 212: Turn the key to the "Off" position. Wait for 10 seconds. Step 213: Turn the key to the "On" position. Wait for 10 seconds. Step 214: Turn the key to the "Off" position. Wait for 10 seconds. Step 215: Turn the key to the "On" position. Wait for 10 seconds. Step 216: Turn the key to the "Off" position. Wait for 10 seconds. Step 217: Turn the key to the "On" position. Wait for 10 seconds. Step 218: Turn the key to the "Off" position. Wait for 10 seconds. Step 219: Turn the key to the "On" position. Wait for 10 seconds. Step 220: Turn the key to the "Off" position. Wait for 10 seconds. Step 221: Turn the key to the "On" position. Wait for 10 seconds. Step 222: Turn the key to the "Off" position. Wait for 10 seconds. Step 223: Turn the key to the "On" position. Wait for 10 seconds. Step 224: Turn the key to the "Off" position. Wait for 10 seconds. Step 225: Turn the key to the "On" position. Wait for 10 seconds. Step 226: Turn the key to the "Off" position. Wait for 10 seconds. Step 227: Turn the key to the "On" position. Wait for 10 seconds. Step 228: Turn the key to the "Off" position. Wait for 10 seconds. Step 229: Turn the key to the "On" position. Wait for 10 seconds. Step 230: Turn the key to the "Off" position. Wait for 10 seconds. Step 231: Turn the key to the "On" position. Wait for 10 seconds. Step 232: Turn the key to the "Off" position. Wait for 10 seconds. Step 233: Turn the key to the "On" position. Wait for 10 seconds. Step 234: Turn the key to the "Off" position. Wait for 10 seconds. Step 235: Turn the key to the "On" position. Wait for 10 seconds. Step 236: Turn the key to the "Off" position. Wait for 10 seconds. Step 237: Turn the key to the "On" position. Wait for 10 seconds. Step 238: Turn the key to the "Off" position. Wait for 10 seconds. Step 239: Turn the key to the "On" position. Wait for 10 seconds. Step 240: Turn the key to the "Off" position. Wait for 10 seconds. Step 241: Turn the key to the "On" position. Wait for 10 seconds. Step 242: Turn the key to the "Off" position. Wait for 10 seconds. Step 243: Turn the key to the "On" position. Wait for 10 seconds. Step 244: Turn the key to the "Off" position. Wait for 10 seconds. Step 245: Turn the key to the "On" position. Wait for 10 seconds. Step 246: Turn the key to the "Off" position. Wait for 10 seconds. Step 247: Turn the key to the "On" position. Wait for 10 seconds. Step 248: Turn the key to the "Off" position. Wait for 10 seconds. Step 249: Turn the key to the "On" position. Wait for 10 seconds. Step 250: Turn the key to the "Off" position. Wait for 10 seconds. Step 251: Turn the key to the "On" position. Wait for 10 seconds. Step 252: Turn the key to the "Off" position. Wait for 10 seconds. Step 253: Turn the key to the "On" position. Wait for 10 seconds. Step 254: Turn the key to the "Off" position. Wait for 10 seconds. Step 255: Turn the key to the "On" position. Wait for 10 seconds. Step 256: Turn the key to the "Off" position. Wait for 10 seconds. Step 257: Turn the key to the "On" position. Wait for 10 seconds. Step 258: Turn the key to the "Off" position. Wait for 10 seconds. Step 259: Turn the key to the "On" position. Wait for 10 seconds. Step 260: Turn the key to the "Off" position. Wait for 10 seconds. Step 261: Turn the key to the "On" position. Wait for 10 seconds. Step 262: Turn the key to the "Off" position. Wait for 10 seconds. Step 263: Turn the key to the "On" position. Wait for 10 seconds. Step 264: Turn the key to the "Off" position. Wait for 10 seconds. Step 265: Turn the key to the "On" position. Wait for 10 seconds. Step 266: Turn the key to the "Off" position. Wait for 10 seconds. Step 267: Turn the key to the "On" position. Wait for 10 seconds. Step 268: Turn the key to the "Off" position. Wait for 10 seconds. Step 269: Turn the key to the "On" position. Wait for 10 seconds. Step 270: Turn the key to the "Off" position. Wait for 10 seconds. Step 271: Turn the key to the "On" position. Wait for 10 seconds. Step 272: Turn the key to the "Off" position. Wait for 10 seconds. Step 273: Turn the key to the "On" position. Wait for 10 seconds. Step 274: Turn the key to the "Off" position. Wait for 10 seconds. Step 275: Turn the key to the "On" position. Wait for 10 seconds. Step 276: Turn the key to the "Off" position. Wait for 10 seconds. Step 277: Turn the key to the "On" position. Wait for 10 seconds. Step 278: Turn the key to the "Off" position. Wait for 10 seconds. Step 279: Turn the key to the "On" position. Wait for 10 seconds. Step 280: Turn the key to the "Off" position. Wait for 10 seconds. Step 281: Turn the key to the "On" position. Wait for 10 seconds. Step 282: Turn the key to the "Off" position. Wait for 10 seconds. Step 283: Turn the key to the "On" position. Wait for 10 seconds. Step 284: Turn the key to the "Off" position. Wait for 10 seconds. Step 285: Turn the key to the "On" position. Wait for 10 seconds. Step 286: Turn the key to the "Off" position. Wait for 10 seconds. Step 287: Turn the key to the "On" position. Wait for 10 seconds. Step 288: Turn the key to the "Off" position. Wait for 10 seconds. Step 289: Turn the key to the "On" position. Wait for 10 seconds. Step 290: Turn the key to the "Off" position. Wait for 10 seconds. Step 291: Turn the key to the "On" position. Wait for 10 seconds. Step 292: Turn the key to the "Off" position. Wait for 10 seconds. Step 293: Turn the key to the "On" position. Wait for 10 seconds. Step 294: Turn the key to the "Off" position. Wait for 10 seconds. Step 295: Turn the key to the "On" position. Wait for 10 seconds. Step 296: Turn the key to the "Off" position. Wait for 10 seconds. Step 297: Turn the key to the "On" position. Wait for 10 seconds. Step 298: Turn the key to the "Off" position. Wait for 10 seconds. Step 299: Turn the key to the "On" position. Wait for 10 seconds. Step 300: Turn the key to the "Off" position. Wait for 10 seconds. Step 301: Turn the key to the "On" position. Wait for 10 seconds. Step 302: Turn the key to the "Off" position. Wait for 10 seconds. Step 303: Turn the key to the "On" position. Wait for 10 seconds. Step 304: Turn the key to the "Off" position. Wait for 10 seconds. Step 305: Turn the key to the "On" position. Wait for 10 seconds. Step 306: Turn the key to the "Off" position. Wait for 10 seconds. Step 307: Turn the key to the "On" position. Wait for 10 seconds. Step 308: Turn the key to the "Off" position. Wait for 10 seconds. Step 309: Turn the key to the "On" position. Wait for 10 seconds. Step 310: Turn the key to the "Off" position. Wait for 10 seconds. Step 311: Turn the key to the "On" position. Wait for 10 seconds. Step 312: Turn the key to the "Off" position. Wait for 10 seconds. Step 313: Turn the key to the "On" position. Wait for 10 seconds. Step 314: Turn the key to the "Off" position. Wait for 10 seconds. Step 315: Turn the key to the "On" position. Wait for 10 seconds. Step 316: Turn the key to the "Off" position. Wait for 10 seconds. Step 317: Turn the key to the "On" position. Wait for 10 seconds. Step 318: Turn the key to the "Off" position. Wait for 10 seconds. Step 319: Turn the key to the "On" position. Wait for 10 seconds. Step 320: Turn the key to the "Off" position. Wait for 10 seconds. Step 321: Turn the key to the "On" position. Wait for 10 seconds. Step 322: Turn the key to the "Off" position. Wait for 10 seconds. Step 323: Turn the key to the "On" position. Wait for 10 seconds. Step 324: Turn the key to the "Off" position. Wait for 10 seconds. Step 325: Turn the key to the "On" position. Wait for 10 seconds. Step 326: Turn the key to the "Off" position. Wait for 10 seconds. Step 327: Turn the key to the "On" position. Wait for 10 seconds. Step 328: Turn the key to the "Off" position. Wait for 10 seconds. Step 329: Turn the key to the "On" position. Wait for 10 seconds. Step 330: Turn the key to the "Off" position. Wait for 10 seconds. Step 331: Turn the key to the "On" position. Wait for 10 seconds. Step 332: Turn the key to the "Off" position. Wait for 10 seconds. Step 333: Turn the key to the "On" position. Wait for 10 seconds. Step 334: Turn the key to the "Off" position. Wait for 10 seconds. Step 335: Turn the key to the "On" position. Wait for 10 seconds. Step 336: Turn the key to the "Off" position. Wait for 10 seconds. Step 337: Turn the key to the "On" position. Wait for 10 seconds. Step 338: Turn the key to the "Off" position. Wait for 10 seconds. Step 339: Turn the key to the "On" position. Wait for 10 seconds. Step 340: Turn the key to the "Off" position. Wait for 10 seconds. Step 341: Turn the key to the "On" position. Wait for 10 seconds. Step 342: Turn the key to the "Off" position. Wait for 10 seconds. Step 343: Turn the key to the "On" position. Wait for 10 seconds. Step 344: Turn the key to the "Off" position. Wait for 10 seconds. Step 345: Turn the key to the "On" position. Wait for 10 seconds. Step 346: Turn the key to the "Off" position. Wait for 10 seconds. Step 347: Turn the key to the "On" position. Wait for 10 seconds. Step 348: Turn the key to the "Off" position. Wait for 10 seconds. Step 349: Turn the key to the "On" position. Wait for 10 seconds. Step 350: Turn the key to the "Off" position. Wait for 10 seconds. Step 351: Turn the key to the "On" position. Wait for 10 seconds. Step 352: Turn the key to the "Off" position. Wait for 10 seconds. Step 353: Turn the key to the "On" position. Wait for 10 seconds. Step 354: Turn the key to the "Off" position. Wait for 10 seconds. Step 355: Turn the key to the "On" position. Wait for 10 seconds. Step 356: Turn the key to the "Off" position. Wait for 10 seconds. Step 357: Turn the key to the "On" position. Wait for 10 seconds. Step 358: Turn the key to the "Off" position. Wait for 10 seconds. Step 359: Turn the key to the "On" position. Wait for 10 seconds. Step 360: Turn the key to the "Off" position. Wait for 10 seconds. Step 361: Turn the key to the "On" position. Wait for 10 seconds. Step 362: Turn the key to the "Off" position. Wait for 10 seconds. Step 363: Turn the key to the "On" position. Wait for 10 seconds. Step 364: Turn the key to the "Off" position. Wait for 10 seconds. Step 365: Turn the key to the "On" position. Wait for 10 seconds. Step 366: Turn the key to the "Off" position. Wait for 10 seconds. Step 367: Turn the key to the "On" position. Wait for 10 seconds. Step 368: Turn the key to the "Off" position. Wait for 10 seconds. Step 369: Turn the key to the "On" position. Wait for 10 seconds. Step 370: Turn the key to the "Off" position. Wait for 10 seconds. Step 371: Turn the key to the "On" position. Wait for 10 seconds. Step 372: Turn the key to the "Off" position. Wait for 10 seconds. Step 373: Turn the key to the "On" position. Wait for 10 seconds. Step 374: Turn the key to the "Off" position. Wait for 10 seconds. Step 375: Turn the key to the "On" position. Wait for 10 seconds. Step 376: Turn the key to the "Off" position. Wait for 10 seconds. Step 377: Turn the key to the "On" position. Wait for 10 seconds. Step 378: Turn the key to the "Off" position. Wait for 10 seconds. Step 379: Turn the key to the "On" position. Wait for 10 seconds. Step 380: Turn the key to the "Off" position. Wait for 10 seconds. Step 381: Turn the key to the "On" position. Wait for 10 seconds. Step 382: Turn the key to the "Off" position. Wait for 10 seconds. Step 383: Turn the key to the "On" position. Wait for 10 seconds. Step 384: Turn the key to the "Off" position. Wait for 10 seconds. Step 385: Turn the key to the "On" position. Wait for 10 seconds. Step 386: Turn the key to the "Off" position. Wait for 10 seconds. Step 387: Turn the key to the "On" position. Wait for 10 seconds. Step 388: Turn the key to the "Off" position. Wait for 10 seconds. Step 389: Turn the key to the "On" position. Wait for 10 seconds. Step 390: Turn the key to the "Off" position. Wait for 10 seconds. Step 391: Turn the key to the "On" position. Wait for 10 seconds. Step 392: Turn the key to the "Off" position. Wait for 10 seconds. Step 393: Turn the key to the "On" position. Wait for 10 seconds. Step 394: Turn the key to the "Off" position. Wait for 10 seconds. Step 395: Turn the key to the "On" position. Wait for 10 seconds. Step 396: Turn the key to the "Off" position. Wait for 10 seconds. Step 397: Turn the key to the "On" position. Wait for 10 seconds. Step 398: Turn the key to the "Off" position. Wait for 10 seconds. Step 399: Turn the key to the "On" position. Wait for 10 seconds. Step 400: Turn the key to the "Off" position. Wait for 10 seconds. Step 401: Turn the key to the "On" position. Wait for 10 seconds. Step 402: Turn the key to the "Off" position. Wait for 10 seconds. Step 403: Turn the key to the "On" position. Wait for 10 seconds. Step 404: Turn the key to the "Off" position. Wait for 10 seconds. Step 405: Turn the key to the "On" position. Wait for 10 seconds. Step 406: Turn the key to the "Off" position. Wait for 10 seconds. Step 407: Turn the key to the "On" position. Wait for 10 seconds. Step 408: Turn the key to the "Off" position. Wait for 10 seconds. Step 409: Turn the key to the "On" position. Wait for 10 seconds. Step 410: Turn the key to the "Off" position. Wait for 10 seconds. Step 411: Turn the key to the "On" position. Wait for 10 seconds. Step 412: Turn the key to the "Off" position. Wait for 10 seconds. Step 413: Turn the key to the "On" position. Wait for 10 seconds. Step 414: Turn the key to the "Off" position. Wait for 10 seconds. Step 415: Turn the key to the "On" position. Wait for 10 seconds. Step 416: Turn the key to the "Off" position. Wait for 10 seconds. Step 417: Turn the key to the "On" position. Wait for 10 seconds. Step 418: Turn the key to the "Off" position. Wait for 10 seconds. Step 419: Turn the key to the "On" position. Wait for 10 seconds. Step 420: Turn the key to the "Off" position. Wait for 10 seconds. Step 421: Turn the key to the "On" position. Wait for 10 seconds. Step 422: Turn the key to the "Off" position. Wait for 10 seconds. Step 423: Turn the key to the "On" position. Wait for 10 seconds. Step 424: Turn the key to the "Off" position. Wait for 10 seconds. Step 425: Turn the key to the "On" position. Wait for 10 seconds. Step 426: Turn the key to the "Off" position. Wait for 10 seconds. Step 427: Turn the key to the "On" position. Wait for 10 seconds. Step 428: Turn the key to the "Off" position.

alarm system less touchy. These are built into the main control unit of the alarm system.Rheostat: Using a small screwdriver, you can loosen up a bolt that adjusts the resistance in the sensor, making it more or less sensitive. These sensors are mounted externally.4Check if the alarm is the reason your car won't stop. When a car refuses to start, most people go through a series of checks to find the issue. After all the checks lead to no solution, consider checking the car alarm. Some alarms are wired with the ignition as an anti-theft measure. Attempt to disable or reset the alarm, and then try starting your car.[6] Advertisement Add New Question Question How do you reset an aftermarket alarm? Audra Fordin Certified Automotive TechnicianAudra Fordin is a Certified Automotive Technician, the Founder of Women Auto Know, and the Owner of Great Bear Auto Repair in Flushing, New York. With more than 38 years of experience, she has intensive knowledge about foreign and domestic auto repairs. Audra has been featured on numerous news and talk shows such as The Today Show, Inside Edition, and Anderson Cooper. Aftermarket alarms have a reset button that's typically found on the left side knee board or underneath the hood by the fuse box. Question How do I turn off the seat belt alarm on my car? In most cars, you have to get under the seat and unplug the plug underneath it to disable the seatbelt alarm. Question My 2001Tahoe alarm sounds whenever I unlock and open the door. I don't have a remote door lock. What can I do to stop the alarm from triggering? When I had this problem, I was told to insert the key into the door, turn it quickly and to the left three times, and then to the right once. This will turn off the alarm. If you're quick you can also get into the vehicle and turn on the engine to stop the alarm from sounding. Unfortunately you'll have to do either option each time you unlock your car. See more answers Ask a Question Advertisement Thanks Thanks Advertisement Co-authored by: Certified Automotive Technician This article was co-authored by Audra Fordin. Audra Fordin is a Certified Automotive Technician, the Founder of Women Auto Know, and the Owner of Great Bear Auto Repair in Flushing, New York. With more than 38 years of experience, she has intensive knowledge about foreign and domestic auto repairs. Audra has been featured on numerous news and talk shows such as The Today Show, Inside Edition, and Anderson Cooper. This article has been viewed 1,221,620 times. Co-authors: 17 Updated: May 23, 2025 Views:1,221,620 Categories: Car Electronics PrintSend fan mail to authors Thanks to all authors for creating a page that has been read 1,221,620 times. "Was very helpful." Share your story

Automatic reset. Reset auto service. Aut. reset fabrieksinst. How to reset the security system in a car. Auto alarm uitschakelen.