Continue



```
If working with Basic4Android and looking for an easy fix to the problem, try this it works both Google marker GooglemLoc=" &[Latitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","[Elongitude]&",15z" GooglemRute=" &[FrmLatt]&","&
subscribers. Become an Insider and start reading now. Embedding a Google Map into a personal website or blog is a simple way to help visitors navigate an area or easily find directions to a location. Google Map into a personal website's code.
You can embed a map view image, a street view image, or even specific directions for a route. Here's how to do it. How to embed a Google Map 1. Type Maps.Google.com into your web browser. 2. Go to the directions, map view, or street view image, a street view image, a street view image, a street view image, or even specific directions for a route. Here's how to do it.
lines. Click on the Menu icon. Kelly Laffey/Business Insider 4. Click on "Share or embed map." Find the option toward the bottom to share or embed. Kelly Laffey/Business Insider 5. The pop-up box will automatically highlight the "Send a link" tab, which enables users to email the map, or to share it on Facebook or Twitter. To get the map's HTML
code, select the "Embed a Map" tab. 6. You can choose the size of the map (small, medium, large, or custom size) by clicking on the drop-down menu next to the HTML code in the box, and paste it into the HTML section of your website. By
embedding a map, you are agreeing to Google's terms of service. Note that live traffic information and other data may not be available in embedded maps. Related coverage from How To Do Everything: Tech: If working with Basic4Android and looking for an easy fix to the problem, try this it works both Google maps and Openstreet even though OSM
creates a bit of a messy result and thanx to [yndolok] for the google marker GooglemLoc=" &[Latitude]&","&[FrmLong]&"/@"&[ScreenX]&","&[ScreenY]&",14z/data=!3m1!4b1!4m2!4m1!3e0?hl=en" 'route ?hl=en 'route ?hl=en
OpenStreetLoc=" 16/"&[Latitude]&"/"&[Longitude]&"/"&[Longitude]&"/"&[Longitude]&"/"&[Longitude]&"/"&[Longitude]&"/"app in iOS or macOS. Unlike some
schemes, map URLs do not start with a "maps" scheme identifier. Instead, map links are specified as regular http links and are opened either in Safari or the Maps app on the target platform. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each. Table 5-1 lists the supported parameters along with a brief description of each.
type. If you don't specify one of the documented values, the current map type is used.qThe query. This parameter is treated as if its value had been typed into the Maps search field by the user. Note that q=* is not supportedThe q parameter can also be used as a label if the location is explicitly defined in the ll or address parameters. A URL-encoded
string that describes the search object, such as "pizza," or an address to be geocodedaddress. Using the address string that geolocation can understand.nearA hint used during search. If the sll parameter is missing or its value is
 incomplete, the value of near is used instead. A comma-separated pair of floating point values that represent latitude and longitude (in that order). IIThe location when you use the q parameter to specify a name. A comma-separated pair of floating point values
that represent latitude and longitude (in that order). zThe zoom level. You can use the z parameter only when you also use the ll parameters. A floating point value between 2 and 21 that defines the area around the center point that should be displayed. spnThe area around the
center point, or span. The center point is specified by the ll parameter. You can't use the span parameter in combination with the z parameter in combination with the z parameter. A coordinate span (see MKCoordinate span (see MKCoordinate span) denoting a latitudinal delta and a longitudinal del
saddr, daddr, and dirflg parameters, but only the daddr parameter is required. If you don't specify a value for saddr, the starting point is "here." An address string that geolocation can understand.daddr parameter is required. If you don't specify a value for saddr, the starting point is "here." An address string that geolocation can understand.daddr parameter is required. If you don't specify a value for saddr, the starting point is "here." An address string that geolocation can understand.daddr parameter is required. If you don't specify a value for saddr, the starting point is "here." An address string that geolocation can understand.daddr parameter is required. If you don't specify a value for saddr, and dirflg parameters, but only the daddr parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required. If you don't specify a value for saddr, and dirflg parameter is required.
parameters, but only the daddr parameter is required. An address string that geolocation can understand. dirflg parameter is ignored; but only the daddr parameter is required. If you don't specify one of the documented transport type values, the dirflg parameter is ignored;
if you don't specify any value, Maps uses the user's preferred transport type or the previous setting.sllThe search location. You can specify the sll parameter by itself or in combination with the q parameter by itself or in combination with the q parameter. For example, is a valid query. A comma-separated pair of floating point values that represent latitude and longitude (in that order). sspnThe screen
span. Use the sspn parameter to specify a span around the search location specified by the sll parameter. A coordinate span (see MKCoordinate span delta. You can use the maps URL scheme to help the user: Perform a search delta. You can use the maps URL scheme to help the user: Perform a search form a search form.
properly encoded URL string as the value of the q parameter. For example: To specify a location for search, you can supply a value for the map type using the t parameter, as shown here: To provide navigation directions from one location to
another, supply the start and destination addresses in the saddr and destination addresses than is shown here. You can use the dirflg parameter as shown here. You can omit the start address when you want to provide directions "from
here." The following example shows a search from here that provides driving directions in a hybrid map. To display a specific location, use the ll parameter to center the map at the specified position as shown here: Another way to display a location is to specify an address, such as: If you use both the ll and address parameters, ll takes precedence over
address. If you include a name in the value of the q parameter, Maps tries to match the name at the specified location. Whether it's through a messenger app, a local context discovery app, a logistics and transportation platform, a travel
planner, or a real estate listing platform, users often need to quickly view location details or find the best route from A to B. While developers can build their own in-app experience, leveraging the comprehensive and familiar interface of Google Maps provides a superior experience. A well-structured Google Maps URL is essential for a seamless user
 experience. Incorrect URLs compromise this experience, directing users to the wrong location, displaying a generic map view instead of specific details, or even with a valid Maps URL, a user expecting details about a specific business
might instead land on a general map view with no relevant information. See example below: This Maps URL is valid for opening Google Maps and displaying a location based on latitude and longitude. However it does not provide users with details about a specific place. Search only using latitude and longitude an
with Google Maps through accurate URLs A Maps URL with a unique place name directs users to that place's details page on Google Maps Platform (GMP) offers two primary methods for constructing accurate URLs. Places API(New), which requires an API key, and Maps URLs, which are free and don't require a key. The following
solutions address different scenarios and use cases: The GMP Places API(New) returns a comprehensive set of information about a specific place. When requesting the googleMapsLinks field (by specifying it in field mask), the API response includes a place object. This object contains pre-formatted URLs, which can be used to
directly open the corresponding view, such as place details view, in Google Maps. Example: Place Details Reguest curl -X GET -H 'Content-Type: application/json'\-H "X-Goog-FieldMask: googleMapsUri,googleMapsUri,googleMapsUri": "googleMapsUri": "googleMapsUri": "googleMapsUri": "googleMapsUri": "googleMapsUri": "googleMapsUri": "googleMapsUri": "googleMapsUri,googleMapsUri": "googleMapsUri": "go
 '/data=!4m7!4m6!1m1!4e2!1m2!1m1!1s0x6b12ae665e892fdd:0x3133f8d75a1ac251!3e0", "placeUri": " !4m3!3m2!1s0x6b12ae665e892fdd:0x3133f8d75a1ac251!12e1", "reviewsUri": " !4m4!3m3!1s0x6b12ae665e892fdd:0x3133f8d75a1ac251!9m1!1b1", "photosUri": " !4m3!3m2!1s0x6b12ae665e892fdd:0x3133f8d75a1ac251!9m1!1b1", "photosUri": " !4m3!3m2!1s0x6b12ae665e892fdd:0x3133f8d75a1ac251!9m1!9m1!1b1", "photosUri": " !4m3!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1!9m1
 !4m3!3m2!1s0x6b12ae665e892fdd:0x3133f8d75a1ac251!10e5" } } ChIJ3S-JXmauEmsRUcIaWtf4MzE in the above example is the Place ID is a textual identifier that uniquely identifies a place in the Google Places database and on Google Maps. Retrieving Place IDs at zero cost To
programmatically retrieve Place IDs, you can use the Place API Text Search(ID Only) functionality. This is a zero cost method for obtaining Place IDs. Learn more about Place ID, and Place API Text Search(ID Only) functionality. This is a zero cost method for obtaining Place IDs. Learn more about Place IDs. Le
Goog-Api-Key: YOUR API KEY' \ -H 'X-Goog-FieldMask: places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id' \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text Search(ID Only) Response: { "places.id" \ ' searchText' Places API Text' Places API Tex
When using the Places API, developers can simply extract the google Maps Uri or google Maps Links field from the response and use it to launch the corresponding view in Google Maps to display directions from the user's current location to this
place place Uri Link to open Google Maps to the place details page for this place writeAReviewUri Link to open Google Maps to the reviews page for this place reviews page for this place and try
the feature today. Utilizing the Maps URLs Using Maps URLs Using Maps URLs Using Maps URLs, you can build a universal, cross-platform URL to launch Google Maps and perform searches, get directions and navigation, and display map views and panoramic images. The URL syntax is the same regardless of the platform in use. You don't need a Google API key to use Maps URLs. The
map actions available are: The Search function launches a Google Maps app or in a browser if the app is not installed that displays directions function launches a Google Maps app or in a browser if the app is not installed that displays directions
between points or enables turn-by-turn navigation on Google Maps for mobile devices. The Street View panorama function lets you launch a viewer to display Street View images as interactive panoramas. Visit GMP Maps URLs:
Displaying place details on Google Maps. This section explains how to construct URLs that will display details for a specific location on Google Maps. It also details how to work with places that have non-unique names by using Place IDs and precise queries. Providing Directions using Maps URLs: This section explains how to create URLs that will display details for a specific location on Google Maps. It also details how to work with places that have non-unique names by using Place IDs and precise queries.
directions between locations, including directions with multiple waypoints and turn-by-turn navigation. Displaying place details on Google Maps The Search function takes two parameters to complete the places search, which are query (required) and query place id(optional). The query parameter is required for all search requests. It accepts a place
name, or comma-separated latitude/longitude coordinates, or a general search term. The Search URL structure: Scenario 1: Displaying place details for a unique place name in this example, only the place name is specified. This URL opens the details for a unique place name in this example, only the place name in this example name in this example name in the place name in the place
place with a non-unique name. What happens when you search only by this non-unique place name is not unique, this URL opens a list of nearby 7-Eleven locations within the viewport. Users can then choose a specific store to see its details. Place list page for
 searching non-unique name To avoid the list of locations and directly access a specific details page, you can use a more precise method. See next example. Scenario 3: Displaying place details for a non-unique place name when dealing with common place names, a simple name search often returns a list of locations. To directly link to a specific details
page, you can use one of the following methods: Method 1: Using a precise query with Place Name and Address In this URL, the query parameter is formatted as place in the Google Places
database and on Google Maps. Here, ChIJGcmcg7ZC1moRAOacd3HoEwM is the unique Place ID for the specific place. The query parameter is still required but will be only used if Google Maps cannot find the place ID. Scenario 4: Displaying place details using latitude and longitude coordinates as well as the place ID Using the Place ID ensures
Google Maps shows detailed place information. Place IDs, you can use the Place IDs, and Place IDs, you can use the Place IDs, you can use the Place IDs, and Place IDs, and Place IDs, and Place IDs, you can use the Place IDs at zero cost IDs at 
request. Places API Text Search(ID Only) Request: curl -X POST -d '{"textQuery": "Sydney Opera House"}' -H 'X-Goog-FieldMask: places.id' 'searchText' Places API Text Search(ID Only) Response: { "places": [ { "id": "ChIJ3S-JXmauEmsRUcIaWtf4MzE" } ] } Place IDs can also be
retrieved when a user clicks or taps a POI on maps. Find out more details about clickable POI icons(JavaScript, Android, iOS) Conclusion Providing accurate place details page, construct the Search URLs using one of the following recommended formats:
query=PLACE NAME, ADDRESS query=PLACE NAME, latitude, longitude, or query=PLACE ID Avoid using only latitude, longitude will not consistently
 lead to the desired place details page. Instead, it will show the latitude and longitude of the location. Categorical search using Maps URLs In a categorical search, you pass a general search term, and Google Maps attempts to find listings that match your criteria near the location you specify. If no location is specified, Google Maps attempts to find listings that match your criteria near the location you specify. If no location is specified, Google Maps attempts to find
listings nearby your current location. Scenario 1: Nearby places search Categorical search - neaby places The Directions documentation displays the path between two or more specified points on the map, as well as the distance and travel time. It offers developers more control over the directions provided. GMP's Maps URLs Directions documentation
provides detailed instructions on constructing URLs for customized directions. The Directions URL structure: Scenario 1: Finding the best route from the user's current location. In this URL, the origin is omitted. When origin is omitted, the
path defaults to the most relevant starting location, such as device location, if available. If none, the resulting map provides a form to allow a user to enter the origin. The value of origin and destination can be either a place name, address, or comma-separated latitude/longitude coordinates. The travelmode is an optional parameter. It defines the
method of travel. This parameter can be set as: driving walking bicycling two-wheeler transit If no travelmode is specified, the Google Map shows one or more of the most relevant modes for the specified route and/or user preferences. Developers can also specify Place IDs by using origin place id parameter and destination place id. Using a Place ID
is the best guarantee that you will link to the right place IDs, and Place IDs, at zero cost To programmatically retrieve Place IDs, you can use the Places API. Text Search(ID Only) functionality. This is a zero cost method for obtaining Place IDs, you can use the Places API Text Search(ID Only) Request: curl -X
POST -d '{"textQuery": "Sydney Opera House"}' -H 'Content-Type: application/json' -H 'X-Goog-Api-Key: YOUR_API_KEY' -H 'X-Goog-FieldMask: places.id' search(ID Only) Response: { "places": [ { "id": "ChIJ3S-JXmauEmsRUcIaWtf4MzE" } ] } Place IDs can also be retrieved when a user clicks or taps a POI on maps. Find
out more details about clickable POI icons(JavaScript, Android, iOS) Directions from user's current location Scenario 3: Providing Turn-by-Turn Navigation mode if the user's current location (device location) is available and used as the origin (either explicitly
provided or implicitly used when the origin parameter is omitted and it is close to the user's current location The origin is specified and it is close to the user's current location is available Route preview is launched when:
dir action=navigate is not set dir action=navigate is not set dir action=navigate is set and the origin is omitted, and the user's current location dir action=navigate is set and the origin is omitted, and the origin is not close to the user's current location is unavailable on all Google Maps products such as Google Maps Web, and/or between all
destinations. In those cases this parameter will be ignored. Turn-by-Turn Navigation Route Preview Conclusion By correctly constructing the Maps URLs, you can ensure users get the right information they need quickly and efficiently. Always specify the destination, and use Place ID whenever possible for guaranteed accuracy When the goal is to
provide immediate navigation, include dir action=navigate parameter to trigger turn-by-turn navigation will start from the user's current location if the device location is available and used as the origin (either explicitly set or omitted) Choosing the right approach for your application You have two primary options: leveraging the pre-
 formatted URLs provided by the Places API or manually constructing Maps URLs in your application. Each approach has its own set of advantages and disadvantages and disadvantages. Places API: The googleMapsLinks fields in the Place Details response provide ready-to-use URLs. This reduces development time and minimizes the risk of errors in
URL formatting. Provides less control over the configuration of directions, it doesn't support waypoints or advanced customization. Also, it is relatively less straightforward to trigger turn-by-turn navigation directly. Maps URLs: Offers greater flexibility and control. Developers can construct URLs to
display place details and configure various aspects of directions, including adding waypoints, specifying travel modes, and initiating turn-by-turn navigation. Requires a deeper understanding of the URL parameters and structure. Manual construction increases the potential for errors if not done carefully. Improving Maps URLs with UTM parameters
To help Google better understand how developers are integrating Maps URLs and to ensure optimal performance, we encourage you to include UTM tracking parameters in your URL construction. By adding utm_source and utm_campaign parameters, you provide valuable data that allows us to analyze usage patterns and improve the Maps URLs
product. For the utm_source parameter, use the name of your application. The utm_campaign parameter should reflect the user's intended action, such as "location_sharing," "place_details_search," or "directions_request". For example, a URL with UTM parameters might look like this: Consistently using these parameters helps us identify areas for
 improvement, troubleshoot issues more effectively, and ultimately deliver a better experience for all users. Next Steps Suggested further reading: Maps Platform Solutions Engineer If working with Basic4Android and looking for an
easy fix to the problem, try this it works both Google maps and Openstreet even though OSM creates a bit of a messy result and thanx to [yndolok] for the google marker GooglemRute=" &[FrmLong]&","&[FrmLong]&","&[FrmLong]&",@"&
[ScreenX]&","&[ScreenY]&",14z/data=!3m1!4b1!4m2!4m1!3e0?hl=en" 'route ?hl=en OpenStreetRute=" Last week at Google Maps from any app. Over one billion people use the Google Maps
your users' journey—including pointing them to a specific location. Maybe they're ready to buy from you and need to find your nearest store, or they want to set up a meeting place with other users. All of these can be done easily in Google Maps already. What you can do is use Google Maps URLs to link into Google Maps and trigger the functionality
 you or your users need automatically. Google Maps URLs are not new. You've probably noticed that copying our URLs out of a browser works—on some platforms. While we have Android Intents and an iOS URL Scheme, they only work on their native platforms. Wou've probably noticed that copying our URLs out of a browser works—on some platforms. While we have Android Intents and an iOS URL Scheme, they only work on their native platforms.
 to users on that same platform. Cross platform. Cross platformSo to start, we needed a universal URL scheme we could support cross-platform—Android, iOS, and web. A messaging app user should be able to share a location to meet up with their friend without worrying about whether the message recipient is on Android or iOS. And for something as easy as that,
developers shouldn't have to reimplement the same feature with two different libraries either. So when a Google Maps URL is opened, it will be handled by the Google Maps for Android or iOS is available, that's where the user will be taken. Otherwise, Google Maps will open in
a browser. Easy to useGetting started is simple—just replace some values in the URL based on what you're trying to accomplish. That means we made it easy to construct URLs programmatically. Here are a few examples to get you started: Say someone has finished booking a place to stay and need figure out how to get there or see what restaurants
are nearby: The query parameter does what it says: plugs a query in. Here we've specified a place, but if you do the same link with no location it will search near the user clicking it. Try it out: click here for sushi near you. This is similar to our query above, but this time we got back a single result, so it gets additional details shown on the
page:google.com/maps/search/?api=1&query=shoreline+amphitheatre The api parameter (mandatory) specifies the version of Maps URLs that you're using. We're launching version 1.Or if a user has set up their fitness app and want to try out a new route on their bike:www.google.com/maps/dir/?
 api=1&destination=stevens+creek+trail&travelmode=bicycling&dir action=navigate We can specify the travelmode to bicycling, destination to a nearby bike trail, and we're done! And we can also open StreetView directly with a focus of our choice to give a real sense of what a place is like: www.google.com/maps/@?
api=1&map_action=pano&viewpoint=36.0665,-112.0906&heading=85&pitch=10&fov=75 The viewpoint is a LatLng coordinate we want to get imagery for, and heading, pitch, and fov allows you to specify exactly where to look. Need more functionality? Google Maps URLs are great to help your users accomplish some tasks in Google Maps. However,
 when you need more flexibility, customization, or control, we recommend integrating Google Maps into your app or site instead. This is where our more powerful Google Maps APIs come into play. With our feature-rich range of APIs, you can access full functionality and can control your camera, draw shapes on the map, or style your maps to match
your apps, brand, or just for better UI. And if you want to go beyond the map we have metadata on Places, images, and much more. Learn moreWhen you're happy to delegate the heavy lifting and make use of the Google Maps URLs and
the Google Maps APIs! Be sure to share your feedback or any issues in the issue tracker. This page goes through the basic, required steps to start using any of the APIs and SDKs on Google Maps Platform. Quickstart If you have never used the Google Cloud console to create a billing account or a project, click the Get Started button that links to an
interactive setup experience in the Cloud console for new users: Get Started Alternatively, you can also complete the required setup steps by clicking through the following tabs: In the Google Cloud console, on the project selector page Make sure that billing is
 enabled for your Cloud project. Confirm that billing is enabled for your project. Note: While you must set up a Cloud offers a $0.00 charge trial. The trial expires at either end of 90 days or after the account has accrued $300 worth of charges,
 whichever comes first. Cancel anytime. For more information, see Billing account credits and Billing. gcloud projects create "PROJECT" Read more about the Google Maps Platform, you must enable the APIs or SDKs you plan to use with your project. Note that some
 integrations require you to enable multiple APIs/SDKs. If you are not sure which APIs or SDKs to enable one or more APIs or SDKs: See the Google Maps Platform APIs and SDKs that you can enable by going to the Maps API Library page in the Cloud
 button to remove the API or SDK from this project.) The following command enables all of the Maps, Routes, and Places APIs: gcloud services enable \ --project "PROJECT" \ "aerialview.googleapis.com" \ "elevation-backend.googleapis.com" \ "areainsights.googleapis.com" \ "aerialview.googleapis.com" \ aerialview.googleapis.com \ aerialview.googleapi
 "roads.googleapis.com" \ "routeoptimization.googleapis.com" \ "timezone-backend.googleapis.com" \ "static-maps-backend.googleapis.com" \ "static-maps-backend.googleapis.com" \ "timezone-backend.googleapis.com" \ "timezone-backend.googleapis.com" \ "timezone-backend.googleapis.com" \ "static-maps-backend.googleapis.com" \ "timezone-backend.googleapis.com" \ "static-maps-backend.googleapis.com" \ "static-ma
enable the Environment APIs: gcloud services enable \ --project "PROJECT" \ "airquality.googleapis.com" \ "pollen.googleapis.com" \ "pollen.googleap
use your API Key in production, we strongly recommend that you restrict your API key. You can find more information in the product-specific Using API Keys page. The API key is a unique identifier that authenticates requests associated with your project.
To create an API key: Go to the Google Maps Platform > Credentials page. Go to the Credentials page under API key created dialog displays your newly created API key before
 using it in production.) gcloud services api-keys create \ --project "PROJECT" \ --display-name "DISPLAY_NAME" Read more about the Google Cloud $300 free trial. Each
Google Maps Platform SKU provides a specific amount of free monthly usage, shown in the pricing list and described in Google Maps Platform billing. Google Maps Platform billing. Google Maps Platform billing. Google Maps Platform billing. Google Maps Platform SKU provides a specific amount of free monthly usage, shown in the pricing list and described in Google Maps Platform billing. Google Map
Google Maps Platform APIs and SDKs. To learn more, see the Overview, Developer, and Get Started guides for the API or SDK you are interested in. The APIs and SDKs are listed at Google Maps Platform Documentation (by product) and Google Maps Platform APIs (by platform). Except as otherwise noted, the content of this page is licensed under
the Creative Commons Attribution 4.0 License, and code samples are licensed under the Apache 2.0 License. For details, see the Google Developers Site Policies. Java is a registered trademark of Oracle and/or its affiliates. Last updated 2025-06-23 UTC. [[["Easy to understand","easyToUnderstand","thumb-up"],["Solved my
 problem", "solvedMyProblem", "thumb-up"], ["Other", "otherUp", "thumb-up"], ["Too complicated / too many steps", "thumb-down"], ["Out of date", "outOfDate", "thumb-down"], ["Samples / code issue", "samplesCodeIssue", "thumb-down"]
 ["Other","otherDown","thumb-down"]],["Last updated 2025-06-23 UTC."],[["To start using Google Maps Platform, you must create a billing-enabled Cloud project and enable the desired APIs or SDKs."],["An API key is required to authenticate requests and track usage; it's crucial to restrict your API key for production use."],["Google offers a $300 (and the strength of the desired APIs or SDKs."],["An API key is required to authenticate requests and track usage; it's crucial to restrict your API key for production use."],["Google offers a $300 (and the strength of the stre
 free trial for Google Cloud Platform and a $200 monthly credit for Google Maps Platform for eligible accounts."],["This guide provides the essential setup steps; for detailed API or SDK usage, refer to the respective documentation."]]],
Google Cloud console or via Cloud SDK. Next, enable the desired APIs or SDKs through the Maps API Library page or using `gcloud services api-keys create`; it is highly recommended to restrict this key before production use. Users are eligible for billing
credits."]] If working with Basic4Android and looking for an easy fix to the problem, try this it works both Google maps and Openstreet even though OSM creates a bit of a messy result and thanx to [yndolok] for the google marker GooglemLoc=" &[Latitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&","&[Longitude]&
[FrmLatt]&","&[FrmLong]&"/"&[ToLatt]&","&[FrmLong]&"/"&[Longitude]&","&[ScreenY]&",14z/data=!3m1!4b1!4m2!4m1!3e0?hl=en" 'route ?hl=en OpenStreetRute=" If working with Basic4Android and looking for an easy fix to the problem, try this it works both Google maps and
 'route ?hl=en OpenStreetLoc=" 16/"&[Latitude]&"/"&[Longitude]&"/"&[Longitude]&"&layers=N" OpenStreetRute=" If working with Basic4Android and looking for an easy fix to the problem, try this it works both Google marker GooglemLoc=" &
[Latitude]&"+"&[Longitude]&","&[Longitude]&","&[ScreenY]&",15z" GooglemRute=" &[FrmLong]&","&[ScreenY]&",15z" GooglemRute=" Using Maps URLs, you are the conditioned by the conditioned
 can build a universal, cross-platform URL to launch Google Maps and perform searches, get directions and navigation, and display map views and panoramic images. The URL syntax is the same regardless of the platform in use. You don't need a Google API key to use Maps URLs. Universal cross-platform syntax As a developer of an Android app, an
iOS app, or a website, you can construct a common URL, and it will open Google Maps and perform the requested action, no matter the platform in use when the map is opened. On an Android device: If Google Maps app for Android is installed and active, the URL launches Google Maps in the Maps app and performs the requested action. If the
Google Maps app is not installed or is disabled, the URL launches Google Maps in a browser and performs the requested action. If the Google Maps app is not installed, the URL launches Google Maps in a browser and performs the requested action. On an iOS device: If Google Maps in the Maps app for iOS is installed, the URL launches Google Maps in the Maps in the Maps app and performs the requested action. If the Google Maps app for iOS is installed, the URL launches Google Maps in the Maps app and performs the requested action.
browser and performs the requested action. On any other device, the URL launches Google Maps in a browser and performs the requested action. It is recommended that you use a cross-platform URL to launches Google Maps in a browser and performs the requested action. It is recommended that you use a cross-platform URL to launch Google Maps in a browser and performs the requested action. It is recommended that you use a cross-platform URL to launch Google Maps in a browser and performs the requested action. It is recommended that you use a cross-platform URL to launch Google Maps in a browser and performs the requested action. It is recommended that you use a cross-platform URL to launch Google Maps in a browser and performs the requested action.
in use. For features that may only be functional on a mobile platform (for example, turn-by-turn navigation), you may prefer to use a platform-specific option for Android or iOS. See the following documentation: Launching Google Maps and performing a specific action To launch Google Maps and optionally perform one of the supported functions, use
a URL scheme of one of the following forms, depending on the action requested: Search — launch a Google Map that displays a pin for a specific place, or perform a general search and launch a map — launch Google Maps with no markers
or directions: ?api=1&map_action=map¶meters Display a Street View panorama — launch an interactive panorama image: ?api=1&map_action=pano¶meters Important: The parameter api=1 identifies the version of Maps URLs this URL is intended for. This parameter is required in every request. The only valid value is 1. If api=1 is NOT present in
the URL, all parameters are ignored and the default Google Maps app will launch, either in a browser or the Google Maps mobile app, depending on the platform in use (for example, . Constructing valid URLs You must properly encode URLs. Note: For easier reading, this document uses unencoded URLs. You should use your platform's standard URL
libraries to encode them. For example, some parameters use a pipe character (1) as a separator, which you must encode as %7C in the final URL. Other parameters use comma-separated values, such as latitude/longitude coordinates or City, State. You must encode the comma as %2C. Encode spaces with %20, or replace them with a plus sign (+).
Additionally, URLs are limited to 2,048 characters for each request. Be aware of this limit when constructing your URLs. Map actions available are: search, directions, display a map, and display a Street View panorama. You specify the action in the request URL, along with required and optional parameters. As is standard in URLs,
you separate parameters using the ampersand (&) character. For each action, the list of parameters and their possible values are enumerated in the Search across the visible map region. When searching for a specific place, the resulting map puts a pin in the specified location
 and displays available place details. Forming the Search URL Parameters query (required): Defines the place(s) to highlight on the map. The query parameter is required for all search requests. Specify locations as either a place name, address, or comma-separated latitude/longitude coordinates. Strings should be URL-encoded, so an address such as
 "City Hall, New York, NY" should be converted to City+Hall%2C+New+York%2C+NY. Specify general search terms as a URL-encoded string, such as grocery+stores or restaurants+in+seattle+wa. query_place_id (optional): A place ID is a textual identifier that uniquely identifies a place. For the search action, you must specify a query, but you may
 also specify a query_place_id. If you specify both parameters, the query is only used if Google Maps cannot find the place ID. If you are trying to definitively link to a specific establishment, the place id when you query for a specific location
using latitude/longitude coordinates. Search examples Location search for a specific location using a place name, address, or comma-separated latitude/longitude coordinates, and the resulting map displays a pin at that location. These three examples illustrate searches for the same location using different location
 values. Example 1: Searching for the place name "Lumen Field" results in the following map: Example 2: Searching for Lumen Field using only latitude/longitude coordinates results in the following map. Notice that there is a pin in the map, but no additional place information is provided on the map or in the side panel: Example 3: Searching for
construct the Search URLs using one of the following recommended formats: query=PLACE_NAME&query_place_id=PLACE_ID To programmatically retrieve Place ID, and Place ID To programmatically retrieve Place ID To programmatically retrieve Place ID, and Place 
API(New) request. Place IDs can also be retrieved when a user clicks or taps a POI on maps. Find out more details about clickable POI icons (JavaScript, Android, iOS) Categorical search In a categorical search for maps a general search term, and Google Maps attempts to find listings that match your criteria near the location you specify. If no
location is specified, Google Maps attempts to find listings nearby your current location. If you prefer to provide a location for a categorical search, include the location for a categorical search string (for example, pizza+seattle+wa). In this example, a search for pizza restaurants in Seattle, WA, results in the following map: Directions Directions action
displays the path between two or more specified points on the map, as well as the distance and travel time. Forming the Directions URL Parameters origin: Defines the starting point from which to display directions. Defaults to most relevant starting location, such as device location, if available. If none, the resulting map may provide a blank form to
 allow a user to enter the origin. The value can be either a place name, address, or comma-separated latitude/longitude coordinates. A string should be URL-encoded, so an address such as "City Hall, New York, NY" should be converted to City+Hall%2C+New+York%2C+NY. Note: This parameter is optional, unless you specify an origin_place_id in
your URL. If you choose to specify an origin place id, you must also include an origin in the URL. origin place id (optional): A place ID is a textual identifier that uniquely identifies a place. If you are trying to definitively specify an establishment, using a place ID is the best guarantee that you will link to the right place. URLs that use this parameter
 must also include an origin. destination: Defines the endpoint of the directions. If none, the resulting map may provide a blank form to allow the user to enter the destination. The value can be either a place name, address, or comma-separated latitude/longitude coordinates. A string should be URL-encoded, so an address such as "City Hall, New York
NY" should be converted to City+Hall%2C+New+York%2C+NY. Note: This parameter is optional, unless you specify a destination_place_id (optional): A place ID is a textual identifier that uniquely identifies a place. If you
are trying to definitively specify an establishment, using a place ID is the best guarantee that you will link to the right place. URLs that use this parameter must also include a destination. travelmode (optional): Defines the method of travel. Here's the list of options: driving walking: Prefers pedestrian paths and sidewalks, where available. bicycling:
 Routes through bike paths, where available. "Bicycling" refers to human-powered travel mode. two-wheeler: Routes through preferred streets for two-wheeler refers to two-wheeler coverage. transit If no travelmode is specified, the
Google Map shows one or more of the most relevant modes for the specified route and/or user preferences. dir_action=navigate (optional): Launches either turn-by-turn navigation or route preview to the specified destination, based on whether the origin is available. If the user specifies an origin and it is not close to the user's current location, or the
current device location is unavailable, the map launches a route preview. If the user does not specify an origin (in which case the origin defaults to the current device location), or the origin is close to the user's current location, the map launches a route preview. If the user does not specify an origin (in which case the origin is close to the user's current location), or the origin is close to the user's current location, the map launches a route preview. If the user does not specify an origin (in which case the origin is close to the user's current location), or the origin is close to the user's current location.
all destinations; in those cases this parameter will be ignored. waypoints: Specifies one or more intermediary places to route directions through between the origin and destination. Multiple waypoints allowed varies
by the platform where the link opens, with up to three waypoints supported on mobile browsers, and a maximum of nine waypoints supported otherwise. Waypoints are displayed on the map in the same order they are listed in the URL. Each waypoints are displayed on the map in the same order they are listed in the URL.
 should be URL-encoded, so waypoints such as "Berlin, Germany | Paris, France" should be converted to Berlin%2CGermany%7CParis%2CFrance. Notes: Waypoints are not supported on all Google Maps products; in those cases this parameter will be ignored. This parameter is optional, unless you specify waypoint place ids in your URL. If you choose to
specify waypoint_place_ids, you must also include waypoints in the URL. waypoints in the URL. waypoints in the URL waypoints a list of place IDs to match the list of waypoints. Place in the same order as the waypoints, and separated using the pipe
 character "|" ( URL-encoded as %7C). If you are trying to definitively specify certain establishments, place IDs are the best guarantee that you will link to the right places. URLs that use this parameter must also include waypoints. avoid (optional): Sets features that route should try to avoid. It can be set to one or more of these options, separated by a
comma character "," (URL-encoded as %2C): Directions examples a map in directions mode and provides a form to allow the user to enter the origin and destination. The following example launches a map with bicycling directions from the Space Needle to Pike Place Market, in Seattle, WA. The following example launches
a map with two-wheeler directions from Google Mumbai to the Mumbai International Airport. Note: The following example for a two-wheelers. This link works in countries where two-wheelers are supported, see Two-wheeler coverage.. The following example launches
a map with walking directions from Google Sydney, Australia to the Queen Victoria Building. Displaying a map The map action=map (required): Specifies the type of map view to display. Maps and Street View share the same
 endpoint. To ensure a map is displayed, the map action must be specified as map. center (optional): Defines the center of the map window, and accepts latitude/longitude coordinates as comma-separated values (for example, -33.8569,151.2152). zoom (optional): Sets the initial zoom level of the map. Accepted values are whole integers ranging from 0
 (the whole world) to 21 (individual buildings). The upper limit can vary depending on the map data available at the selected location. The default is 15. basemap (optional): Defines an extra layer to display on the map, if any. The value
can be one of the following: none (default), transit, traffic, or bicycling. Map example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location. ?api=1&map_action=map The following example URL launches a default Google Map, centered on the user's current location of the user's curre
degrees of horizontal view (a full wrap-around) and 180 degrees of vertical view (from straight up to straight down). The pano action launches a viewer that renders the camera at its center. You can manipulate the camera to control the zoom and the orientation of the camera. Google Street View provides
panoramic views from designated locations throughout its coverage area. User contributed Photospheres and Street View urange area location are also available. Forming the Street View share the same
 endpoint. To ensure a panorama is displayed, the action must be specified as pano. One of the following URL parameters is also required: viewpoint: The viewpoint location, specified as comma-separated latitude/longitude coordinates (for example 46.414382,10.013988). Because Street Viewpoint location, specified as panorama photographed closest to the viewpoint location, specified as comma-separated latitude/longitude coordinates (for example 46.414382,10.013988). Because Street Viewpoint location, specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be specified as panorama photographed closest to the viewpoint location must be spec
 imagery is periodically refreshed, and photographs may be taken from slightly different positions each time, it's possible that your location may snap to a different panorama when imagery is updated. pano: The specific panorama ID of the image to display. If you specify a pano you may also specify a viewpoint. The viewpoint is only used if Google
 Maps cannot find the panorama ID. If pano is specified but not found, and a viewpoint is NOT specified, no panorama image is displayed. Instead, Google Maps opens in default mode, displaying a map centered on the user's current location. The following URL parameters are optional: heading: Indicates the compass heading of the camera in degr
clockwise from North. Accepted values are from -180 to 360 degrees. If omitted, a default heading is chosen based on the viewpoint (if specified) of the guery and the actual location of the image. pitch: Specified in degrees from -90 to 90. Positive values will angle the camera up, while
negative values will angle the camera down. The default pitch of 0 is set based on on the position of the camera when the image was captured. Because of this, a pitch of 0 is often, but not always, horizontal field of view of the
image. The field of view is expressed in degrees, with a range of 10 - 100. It defaults to 90. When dealing with a fixed-size viewport, the field of view is considered the zoom level, with smaller numbers indicating a higher level of zoom. Street View examples The first two examples display a panorama of the Eiffel Tower. Example one uses only a
viewpoint for the location, and sets the optional heading, pitch, and fov parameters. For comparison, example displays an indoor panorama image. Example 1: Uses only a viewpoint to specify location.?
api=1&map action=pano&viewpoint=48.857832%2C2.295226&heading=-45&pitch=38&fov=80 Example 2: Uses a pano ID as well as a viewpoint location. The pano ID is found, so the viewpoint is ignored. Notice that the panorama image that is displayed for the pano ID is
slightly different, and more recent, than the image found using only the viewpoint. ?api=1&map action=pano&pano=tu510ie z4ptBZYo2BGEJg&viewpoint=48.857832%2C2.295226&heading=-45&pitch=38&fov=80 Example 3: Displays a panorama of the interior of the Sarastro restaurant in London, UK, specified with a panorama ID. ?
api=1&map action=pano&pano=4U-oROCNsC6u7r8qp02sLA Finding a panorama ID To find the ID of a specific panorama image, there are multiple methods you can use. More examples Directions examples Directions examples and display driving directions from Paris, France to Cherbourg,
France, routing through the following waypoints: City, CountryPlace NamePlace ID 1. Versailles, France Chartres, France Chart
Caen Castle ChIJ06tnGbxCCkgRsfNjEQMwUsc In the example URLs, the waypoints are defined in different ways so you can compare the differences in the display of the waypoints defined as City, Country: Example 2: Waypoints defined as City, Country: Example 3: Wayp
Country, and also provides waypoint place ids for a specific establishment in each waypoints as City, Country, but lists the waypoints in the order they are listed in the URL. Map examples Displays a map with a
specified basemap (satellite) and layer (transit). ?api=1&map action=map¢er=37.7992940%2C-122.3976113&zoom=15&basemap=satellite&layer=transit Street View panorama using a FIFE image key as the pano ID. Note that the pano ID is prefaced with F:. ?api=1&map action=pano&pano=F:-ud6AZSB-
sQg/V0cfCSV3OWI/AAAAAAAG1U/UQEoc5sXPQEIP7zzD6SWzmKb8Vbug47uQCLIB&heading=22&pitch=-5&fov=55 Improving Maps URLs with UTM parameters To help Google better understand how developers are integrating Maps URLs with UTM parameters To help Google better understand how developers are integrating Maps URLs with UTM parameters are integrating Maps URLs with UTM parameters.
construction. By adding utm source and utm campaign parameters, you provide valuable data that allows us to analyze usage patterns and improve the Maps URLs product. For the utm source parameter, please use the name of your application. The utm source parameter should reflect the user's intended action, such as "location sharing,"
"place details search," or "directions request." For example, a URL with UTM parameters might look like this: When you want to share a location visually, a map is an effective way to do it. But with Google Maps Platform's mapping options and even the consumer Google Maps apps, there are several approaches to consider. Choosing the right
approach for you comes with different features, costs, and customization options. In this post, we'll cover three popular options and explain when each makes sense to use. Generate a custom map link to send users to the right location on maps.google.comUse the Static Maps API for a non-interactive snapshot of a locationBuild a dynamic map with
the Google Maps JavaScript APIWe'll start with the quickest, simplest map tool, then add a little more complexity with each example to show you the many ways you can customize your map.**Use map links to share locations and directions**Every day, millions of people worldwide use Google Maps to find places to go and things to do while exploring
the world around them. You can also use Google Maps Platform to create links to Google Maps. You can share locations or even complete directions-and it can be as easy as typing in the name of a place. This minimalist option has the added advantage of being completely free, even at high volumes. There is no need for an API Key. And to customize,
you only need to edit a query URL that redirects users to Google Maps. Mobile users are sent the location in the Google Maps app (if installed). Otherwise, the link opens in the provided the location in the query parameter. There are various styles you can use to specify the location. For
example: Note that the map links are all URL encoded, which formats spaces and other characters to easily be passed through URLs. While some browsers may encode the links automatically, it's best to perform this yourself before sharing the map link. Google Maps is often used for directions, so you can build origin and destination into your map link.
gueries. Rather than using the guery parameter, the same values can be included in the origin (where your directions begin) and destination (where your directions begin) are the properties of the 
the origin and a landmark as destination. Or, try leaving the origin empty to include the user's location (or allow them to enter it themselves). You can use map links in text messages, emails, or on your own site. So let's
move on and cover a couple ways to create and display a map.**Mark locations with the Maps Static API**Like the map links option, the Maps Static API also involves building a custom URL. Instead of sending the user directly to the URL, it's used as the source in an HTML image tag. This allows you to mark a location on your website, without the
need to re-route to Google Maps. Once you have an API key, the base URL to start with looks like this: the question mark, you need to add these parameters (at a minimum, documentation lists more options):center: the coordinates or place name of the location where you want the map to be centeredzoom: a value between 1 (world view) and 20
(building view)size: pixel width and height of the map {horizontal_value}x{vertical_value}key: your api key, which should be protected according to these best practicesFor example, here's a map centered on San Francisco:
```